

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26582
Address

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26582
Address

SPORTSMANS SQUARE CIRCLE
Lease or Property Owner
129 CIRCLE DR. FAIRMONT, WV 26554
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE ST. MONONGAH, WV 26582
Complete Address

GLOVER GAP 7.5'
Well Location

MANNINGTON
District

MARION
County

5078
Well No.

SPORTSMANS SQUARE CIRCLE
Farm

STATE INSPECTOR SUPERVISING PLUGGING *William J. Hensley*

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MIKE MITCHELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 25th day of MAY, 2011 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In
Removed 2" tubing from surface to 388'. Cleaned 12 1/4" hole from surface to 330'. Cleaned 9 7/8" hole from 330' to 430' top of 7" casing. Cleaned 6 1/4" hole from 430' to 2086'. Removed 859' of 7" casing from 430' to 1289'. Left 7" casing in hole from 1289' to 2086'. Cut remaining 7" casing at 2086', 1985', 1890', 1790', 1693', 1593', 1493', and 1387'. Cleaned 9 7/8" hole from 330' to 1255'. Cleaned 9 7/8" hole thru Pittsburgh Coal 961' to 968'. Left 14' of 16" conductor in hole from 14' to surface.		16" Conductor 7" Casing 2 3/8" Tubing	0' 864' 388'	14' 797' 0'
Cement hole from 2086' back to surface as follows.				
From 2086' to 1447' with 100 sacks of Super Light Cement.				
From 1447' to 1168' with 70 sacks of 35/65 Cement.				
From 1168' to 861' with 140 sacks of Super Thixotropic Cement with dye. From 861' to surface with 326 sacks of Econofill Cement. A total of 636 sacks of Cement were used. Cement did circulate at surface.				
Coal Seams	Description of Monument			
<u>PITTSBURGH</u>	<u>961' to 968'</u>	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

RECEIVED
Office of Oil & Gas
OCT 17 2011
WV Department of Environmental Protection

... and that the work of plugging and filling said well was completed on the 15th day of JUNE, 2011

And further deponents saith not
OFFICIAL SEAL
STATE OF WEST VIRGINIA
NOTARY PUBLIC
Jacqueline L. Shriver
12 Rousch Drive
Westover, WV 26501
My Commission Exp March 18, 2020

Mike Mitchell
Mike Mitchell
Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 13th day of October, 2011

Jacqueline L. Shriver
Notary Public
Permit No. 47-49-02167-P
Well No. 5078

My commission expires: March 18, 2020

10/21/2011