

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE ST. MONONGAH WV 26554
Address
M.H. PRITCHARD HEIRS (c/o PHILLIP PRITCHARD)
Lease or Property Owner
PO BOX 108 MANNINGTON, WV 26582
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE ST. MONONGAH, WV 26554
Complete Address
MANNINGTON 7.5'
Well Location
MANNINGTON
District
MARION
County
3353
Well No.
PRITCHARD, MILDRED H. HEIRS
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]* 3-9-14

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and **KEVIN S. WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 8th day of November, 2013 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
<p>Cleaned 6 1/2" hole through 7" casing from the surface to 1863'. Tagged solid plug at 1863'. Removed 1246' of 7" casing from the surface to 1246'. Left unknown 7" casing in the hole from 1246' to unknown depth. Cut remaining 7" casing at the following depths: 1857', 1758', 1653', 1547', 1445' and 1348'. Cemented bottom hole from 1863 to 1198' with 85 sacks of Superlite Cement. Removed 834' of 8 5/8" casing from the surface to 846'. Left 324' of 8 5/8" casing in the hole from 846' to 1170'. Cut remaining 8 5/8" casing at the following depths: 1097' and 974'. Cleaned 12 1/2" hole from the surface to 282'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 282' to 846'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 820' to 627'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole through 8 5/8" casing from 846' to 1198'. Tag bottom hole plug at 1198'.</p> <p><u>Cemented hole from top of bottom hole plug at 1198' back to surface as follows:</u> From 1198' to 820' with 175 sacks of Expandable Cement. From 820' to 520' with 140 sacks of Thixotropic Cement with green dye. From 520' to the surface with 225 sacks of Expandable Cement. Cement did circulate at the surface. A total of 635 sacks of cement was used to cement the well from 1863' to the surface. Cement did circulate at the surface. Left 20' of 16" conductor casing in the well from the surface to 20'.</p>				
Coal Seams		Description of Monument		
PITTSBURGH	620' to 627'	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		

RECEIVED
Office of Oil & Gas
MAR 13 2014
WV Department of
Environmental Protection

... And that the work of plugging and filling said well was completed on the 11th day of December, 2013

And further deponents saith not.

[Signature]
Delbert Moore


[Signature]
Kevin S. Wright

Sworn to and subscribed before me this 27th day of January 2014

[Signature]
Notary Public

My commission expires: 11/4/23

Permit No. 47-49-02176-P
Well No. 3353



03/14/2014