FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA **DEPARTMENT OF ENERGY** OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. Coal Operator or Owner 1 BRIDGE STREET MONONGAH, WV 26554 Address **CONSOLIDATION COAL CO.**

Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address

JEFFERY MICHAEL & RONALD C. MICHAEL

Lease or Property Owner P.O. Box 211 Mannington WV 26582 Address

CONSOLIDATION COAL CO. Name of Well Operator

1 BRIDGE STREET MONONGAH, WV 26554

Complete Address **GLOVER GAP 7.5'** Well Location

MANNINGTON District

MARION

County

5240 Well No.

MICHAEL JEFFREY & RONALD

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 14th day of December, 2011 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				· · · · · · · · · · · · · · · · · · ·
Cleaned 12 1/2" hole from the surface to the top of the 10 3/4".		16" Conductor	0,	20'
casing at 173'. Reduced hole to 9 7/8" at 173'. Cleaned 9 7/8" hole				
from 173' to the top of the 8 5/8" casing at 660'. Reduced hole to		10 ¾" Casing	0'	122'
	d 7 7/8" hole from 660' to 1706'. Tagged	·		
plug at 1706'. Removed 8 5/8" casing from 660' to 1251'. Left 83'		8 5/8" Casing	591'	83'
	hole from 1251' to 1334'. Cleaned 9 7/8"			
	the top of the 8 5/8" casing at			
	hole through the Pittsburgh Coal	en en	galang balang	
(856' - 863'). Left 20' of 16" casing in the hole from 20' to surface.		Pril:		5 g
	477001 1 4 4 5 4 H			1,314
	1706' back to surface as follows:			
From 1706' to 1063' with 211 sacks of Super Lite Cement. From 1063' to 756' with 170 sacks of SuperTropic Cement with		[0]	3,33 %	
	th 170 sacks of Super Fropic Cement with			
white dye.	with 205 sacks of Super Lite Coment. A total		in a see Carri ser	100
From 756' to surface with 395 sacks of Super Lite Cement. A total of 776 sacks of cement were used to fill the hole from 1706' back		美術 人 17		
to surface. Cement did circulate at the surface.			Service Control	n.* .
to surface. Cement di	d circulate at the surface.			
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	(856' - 863')	77" of 7" casing w/ company name, well number,		
		permit number and date cemented stated on 7°		
		casing. Well marker will be attached to cement		
		plug at ground level.		

And further deponents saith not.

Delbert Moore

S. Wu Kevin S. Wright

Sworm to and subscribed before me this 17th day of February. 2012

Notary Public

Permit No. 47-049-02195-P

My commission expires:

OFFICIAL SEAL
STATE OF WEST VIRGINIA
NOTARY PUBLIC
Jacqueline L. Shriver
12 Rousch Drive
Westown WV 26501 Westover, WV 26501

Wy Commission Exp. March 18, 2020 =

Well No. <u>5240</u>