STATE OF WEST VIRGINIA **DEPARTMENT OF ENERGY** OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy malled to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. Coal Operator or Owner 1 BRIDGE STREET MONONGAH, WV 26554

Address CONSOLIDATION COAL CO.

Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554 **Address**

WILLIAM C. AND VICKIE E. LUCAS Lease or Property Owner **BOX 144 MANNINGTON, WV 26582** Address

CONSOLIDATION COAL CO. Name of Well Operator

1 BRIDGE STREET MONONGAH, WV 26554 Complete Address

GLOVER GAP 7.5' Well Location

County

Farm

MANNINGTON District MARION

DEC 1 2 2012

RECEIVED

Office of Oil & Gas

<u>5356</u> Well No. LUCAS, WILLIAM C. & VICKIE E.

WV Department of virgamental Protection

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 6th day of August, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Removed 2 3/8" tubing from the surface to 528'. Cleaned 12 1/4" hole from the surface to 249'. Reduced hole to 9 7/8". Cleaned		16" Conductor	0,	20'
9 7/8" hole from 249' to 528'. Removed 2 3/8" tubing from 528' to 924' with extreme difficulty. Cleaned 9 7/8" hole from 528' to top of		8 5/8" Casing	169'	450'
existing 8 5/8" casing at 924'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 924' to 1561'. Tagged plug at 1561'. Removed 169' of 8 5/8" casing from 924' to 1093'. Left 450' of 8 5/8" casing in the hole from 1093' to 1543'. Cut remaining 8 5/8" casing at the following depths; 1450', 1350', 1267' and 1167'. Cleaned 9 7/8" hole from 924' to 1093'. Cleaned 9 7/8" hole through Pittsburgh Coal (1046' – 1054'). Left 20' of 16" conductor pipe in the hole from 20' to surface.		2 3/8" Tubing	924	O,
From 1561' to 1254' wi 1254' to 946' with 98 si dye. From 946' to surfa A total of 598 sacks of	1561' back to surface as follows; th 60 sacks of Super Lite Cement. From acks of SuperTropic Cement with white ace with 440 sacks of Super Lite Cement. cement were used to fill the hole from Cement did circulate at the surface.			
Coal Seams		Description of Monument		
Pittsburgh	(1046' - 1054')	77" of 7" casing w/ company name, well number,		
		permit number and date cemented stated on 7"		
		casing. Well marker will be attached to cement		
		plug at ground level.		

... and that the work of plugging and filling said well was completed on the 15th day of October, 2012

And further deponents saith not.

Sworn to and subscribed before me this 3th day of Declinutes, 2012

My commission expires:

March 18, 2020

STATE OF WEST VIRGINIA
NOTARY PUBLIC
Jacqueline L. Shriver
12 Rousch Drive
Westover, WY 26501
My Commission Exp. March 18, 2020

Permit No. <u>47-049-02231-P</u> Well No. 5356