FORM WR-38 (Affidavit of Plugging)

## STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

## AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address

CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address

JEFFREY MICHAEL
Lease or Property Owner

P.O BOX 211 MANNINGTON, WV 26582

CONSOLIDATION COAL CO.

Name of Well Operator

1 BRIDGE STREET MONONGAH, WV 26554

Complete Address

GLOVER GAP 7.5'

Well Location

MANNINGTON

District

MARION

County

5254

Well No.

MICHAEL JEFFERY
Farm

STATE INSPECTOR SUPERVISING PLUGGING\_

Address

**AFFIDAVIT** 

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

<u>DELBERT MOORE</u> and <u>KEVIN WRIGHT</u> being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 28<sup>th</sup> day of December, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In	
Formation  Cleaned 12 ¼" hole from the surface to 205'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 205' to 1076'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 1076' to 1079'. Reduced hole to 6 ¼". Cleaned 6 ½" hole from 1079' to 1084'. Tagged solid plug at at 1084'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 755' to 764'. Left 20' of 16" conductor casing in the hole from the surface to 20'.  Cemented hole from 1084' back to surface as follows: From 1084' to 855' 124 sacks of Super Tropic Cement with white dye. From 655' to surface with 384 sacks of SuperLite Cement. A total of 488 sacks of cement were used to fill the hole from 1084' back to surface. Cement did circulate at the surface.		Jince	of Oil & Of Oil & Of 201 Partme Intal Pro	Gas	
Coal Seams		Description of Monument			
<u>Pittsburgh</u>	(755' - 764')	77° of 7° casing w/ company name, well number,			
		permit number and date cemented stated on 7"			
			will be attached to cement		
		plug at ground level.			

... and that the work of plugging and filling said well was completed on the 8th day of January, 2013

And further deponents saith not.

Delbert Moore

Kulin S. Wiight

Kevin S. Wright

Sworn to and subscribed before me this 28th day of Feb 2013

Carole A Mayle

Notary Public

Permit No. <u>47-049-02233-P</u> Well No. <u>5254</u> 03/08/2013

My commission expires: 9-12