

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address  
CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address  
JEFFREY MICHAEL  
Lease or Property Owner  
P.O BOX 211 MANNINGTON, WV 26582  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE STREET MONONGAH, WV 26554  
Complete Address  
GLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
5140  
Well No.  
MICHAEL, JEFFERY  
Farm

STATE INSPECTOR SUPERVISING PLUGGING [Signature]  
AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

MIKE MITCHELL and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 13<sup>th</sup> day of November, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Cleaned 12 1/4" hole from the surface to top of 10 3/4" casing at 203'. Reduced hole to 9 7/8" at 203'. Cleaned 9 7/8" hole from 203' to top of 7" casing at 682'. Reduced hole to 6 1/4" at 682'. Cleaned 6 1/4" hole from 682' to 2215'. Bottom of 7" casing is at 2004'. Tagged plug at 2215'. Cut 7" casing at the following depths; 1904', 1804', 1704', 1604', 1504 and 1404'. Cemented bottom hole from 2215' to 1657' with 85 sacks of 35/65 Poz Mix Cement. Removed 7" casing with extreme difficulty from 682' to 1359'. Remaining 7" casing could not be removed due to the casing being bonded in the hole. Cleaned 9 7/8" hole to top of 8 5/8" casing at 1167'. 8 5/8" casing could not be removed due to a cement bond. Multistring cut 7" and 8 5/8" casings at 1430'. Left an unknown amount of 8 5/8" casing in the hole from 1167' to an unknown depth. Cut remaining 8 5/8" casing at 1350', 1275' and 1205'. Left 40' of 10 3/4" casing in the hole from 203' to 243'. Cleaned 9 7/8" hole through Pittsburgh Coal (1048' to 1056'). Left 12' of 16" conductor pipe in the hole from 12' to surface. <b>Cemented hole from 2215' back to surface as follows:</b> From 2215' to 1657' with 85 sacks of 35/65 Poz Mix Cement. From 1657' to 1256' with 77 sacks of SuperLite Cement. From 1256' to 948' with 140 sacks of Thixotropic Cement with dye. From 948' to surface with 456 sacks of SuperLite Cement. A total of 758 sacks of cement were used to fill the hole from 2215' back to surface. Cement did circulate at the surface.	16" Conductor	0'	20'	
		10 3/4" Casing	0'	40'
		8 5/8" Casing	0'	Unknown
		7" Casing	669'	645'
<b>Coal Seams</b>		<b>Description of Monument</b>		
<u>Pittsburgh</u>	(1048' - 1056')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

RECEIVED  
Office of Oil & Gas  
JAN 28 2013  
WV Department of Environmental Protection

... and that the work of plugging and filling said well was completed on the 20<sup>th</sup> day of December, 2012

And further deponents saith not.

[Signature]  
Mike Mitchell

[Signature]  
Kevin S. Wright

Sworn to and subscribed before me this 14 day of January 2013

[Signature]  
Notary Public

My commission expires:  
March 18, 2020



Permit No. 47-049-02234-P  
Well No. 5140

02/01/2013