

ORIGINAL

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
RONALD A. & PRISCILLA A. HAMILTON
Lease or Property Owner
3 BEHLAR ROAD FAIRVIEW, WV 26570
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
5344
Well No.
HAMILTON, RONALDA. & PRISCILLA A. HAMILTON
Farm

STATE INSPECTOR SUPERVISING PLUGGING 

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:


DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 3rd day of April, 2013 and that the well was plugged in the following manner:



Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Cleaned 12 1/2" hole from the surface to 523'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 523' to 1327'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 1327' to 1328'. Reduced hole to 6 1/2". Cleaned 6 1/2" hole from 1328' to 1344'. Tagged solid plug at 1344'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 1084' to 1091'. Left 40' of 16" conductor casing in the hole from the surface to 40'.		16" Conductor	0'	40'
<u>Cemented hole from 1344' back to surface as follows:</u> From 1344' to 984' with 191 sacks of SuperTropic Cement with white dye. From 984' to surface with 606 sacks of SuperLite Cement. A total of 797 sacks of cement were used to fill the hole from 1344' back to surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	<u>(1084' - 1091')</u>	<u>77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.</u>		

RECEIVED
Office of Oil & Gas
JUN 24 2013
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 15th day of April, 2013

And further deponents




Delbert Moore

Kevin S. Wright

Sworn to and subscribed before me this 3rd day of June


Notary Public

My commission expires: Feb. 16, 2021

Permit No. 47-049-02243-P
Well No. 5344

07/19/2013