FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA **DEPARTMENT OF ENERGY** OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy malled to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554 Address CONSOLIDATION COAL CO.

Coal Operator or Owner 1 BRIDGE STREET MONONGAH, WV 26554

Address

THOMAS LEE SNODGRASS Lease or Property Owner 291 EVANS RUN ROAD MANNINGTON, WV 26582 **Address**

CONSOLIDATION COAL CO.
Name of Well Operator

1 BRIDGE STREET MONONGAH, WV 26554

Complete Address **GLOVER GAP 7.5' Well Location** MANNINGTON

District MARION County 5461

Well No. SNODGRASS, THOMAS LEE

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA. County of MONONGALIA ss:

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 29th day of July, 2013 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				LOIL III
Cleaned 12 ½" hole from the surface to 274'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 274' to 1292'. Reduced hole to 6 ½". Clean 6 ½" hole from 1292' to 1398'. Tag solid plug at 1398'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 1021' to 1027'. Left 20' of 16" conductor casing in the hole from the		16" Conductor	0'	20,
surface to 20'.		DEC	EIVED	
_		nec		.
Cemented hole from 1398' back to surface as follows: From 1398' to 1227' with 50 sacks of 35/65 Poz Cement. From 1227' to 921' with 135 sacks of Thixatropic Cement with yellow dye. From 921' to surface with 286 sacks of Econofill Cement. A total of 471 sacks of cement were used to fill the hole from 1398' back to surface. Cement did circulate at the surface.		Office of	OII & C	as
			3 0 2013	
		WV Der Environme	artmer	t of
		Fardinania (atal Dro	tection
		Environme	llairic	
Coal Seams		Description of Monument		
<u>Pittsbargh</u>	(1021' - 1027')	77° of 7° casing w/ company name, well number, permit number and date cemented stated on 7°		
		casing. Well marker will be attached to cement		
and that the work of	plugging and filling sold will be	plug at ground level.		

... and that the work of plugging and filling said well was completed on the 27th day of August, 2013

And further deponents saith not.

Kevin S. Wright

Sworn to and subscribed before me this 20 day of Sept.

Notary Public

My commission expires: 2

OFFICIAL SEAL STATE OF WEST VIRGINIA NOTARY PUBLIC MONICA DeFELICE RR 3 Box 170C Gratton, WV 26354 My Commission Expires February 16, 2021

Permit No. 47-049-02254-P Well No. 5461