FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

ORIGINAL

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Weil Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26554
Address
CONSOLIDATION COAL COMPANY
Lease or Property Owner

1 BRIDGE ST MONONGAH, WV 26554
Address

CONSOLIDATION COAL CO.

Name of Well Operator

1 BRIDGE ST. MONONGAH, WV 26554

Complete Address

CLOVER GAP 7.5'

Well Location

MANNINGTON

District

MARION

County

5051

Well No.

CONSOLIDATION COAL COMPANY

Farm

STATE INSPECTOR SUPERVISING PLUGGING RUM

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MIKE MITCHELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 19th day of June, 2013 and that the well was plugged in the following manner:

	Filling Material	Casing	Casing Pulled	Casing Left in	
Formation		Size & Kind			ĺ
Cleaned 12 ¼" hole from the surface to 328'. Reduced hole to 9 7/8'. Cleaned 9 7/8" hole from 328' to 1260'. Reduced hole to 6 ¼". Cleaned 6 ¼" hole from 1260' to 1263'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 920' to 929'.		16" Conductor	0'	19'	
	•			REC	EIVED
Cemented hole from 1263' back to surface as follows; From 1263' to 1129' with Expandable Cement. From 1129' to 820' with 180 sacks of Thixotropic Cement w/ dye. From 820' to surface with Expandable Cement Cement. A total of 480 sacks of Expandable Cement and 180 sacks of Thixotropic Cement was used to cement the hole from 1263' to the surface. Cement did circulate at the surface. Left 19' of 16" conductor casing in the hole from the surface			r	et:	01.5
				8-5	Oil 5 Gas
to 19 ¹ .			\ \M	W Dan	hetmant . s
			Envi	onmen	artment of tal Protection
Coal Seams		Description of Monumer	nt		
PITTSBURGH	920' to 929'	77" of 7" casing w/company name, well number,			1
(Name)		permit number and date cemented stated on 7"			1

... And that the work of plugging and filling said well was completed on the 3rd day of July, 2013

And further deponents saith not.

(Name)

Mike Mitchell

casing. Well marker will be attached to the

cement plug at ground level.

Kevin S. Which

Sworm to and subscribed before me this 22 day of July

Notary Public

My commission expires: February 16, 2021

Permit No. <u>47-49-02264-P</u> Well No. <u>5051</u>