

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address

CONSOLIDATION COAL COMPANY  
Lease or Property Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE ST. MONONGAH, WV 26554  
Complete Address  
CLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
5063  
Well No.  
CONSOLIDATION COAL COMPANY  
Farm

STATE INSPECTOR SUPERVISING PLUGGING *William H. ...*

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

MIKE MITCHELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 13<sup>th</sup> day of August, 2013 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
Cleaned 12 1/2" hole from the surface to 305'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 305' to 1146'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 1146' to 1502' Reduced hole to 6 1/2". Tagged solid plug at 1502' Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 985' to 993'.		16" Conductor	0'	17'
<b>RECEIVED</b> Office of Oil & Gas OCT 30 2013 WV Department of Environmental Protection				
<u>Cemented hole from 1502' back to surface as follows:</u> From 1502' to 1193' with 145 sacks of 35/65 Poz Cement. From 1193' to 885' with 180 sacks of Thixotropic Cement w/ dye. From 885' to surface with 315 sacks of Econofill Cement. A total of 620 sacks of cement were used to cement the hole from 1502' to the surface. Cement did circulate at the surface. Left 17' of 16" conductor casing in the hole from the surface to 17'.				
<b>Coal Seams</b>		<b>Description of Monument</b>		
<u>PITTSBURGH</u>	985' to 993'	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

... And that the work of plugging and filling said well was completed on the 29<sup>th</sup> day of August, 2013

And further deponents saith not.

*Mike Mitchell*  
Mike Mitchell


*Kevin S. Wright*  
Kevin S. Wright

Sworn to and subscribed before me this 30 day of Sept.

*Monica DeFelice*  
Notary Public

My commission expires: 2/16/21

Permit No. 47-49-02269-P  
Well No. 5063



11/01/2013