

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address  
CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address  
THOMAS LEE SNODGRASS  
Lease or Property Owner  
291 EVANS RUN ROAD MANNINGTON, WV 26582  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE STREET MONONGAH, WV 26554  
Complete Address  
GLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
5462  
Well No.  
SNODGRASS, THOMAS LEE  
Farm

STATE INSPECTOR SUPERVISING PLUGGING *William H. ...*

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 3<sup>rd</sup> day of September, 2013 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Cleaned 12 1/4" hole from the surface to 348'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 348' to 1061'. Removed 115' of 7" casing from 1061' to 1176' with extreme difficulty due to being parted. Continued to clean 9 7/8" hole from 1061' to 1308'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 1090' to 1097'. Reduced hole to 6 1/4". Cleaned 6 1/4" hole from 1308' to 2193'. Left 844' of 7" casing in the hole from 1308' to 2152'. Cut remaining 7" casing at the following depths: 2111', 2011', 1912', 1812', 1700', 1613', 1514' and 1414'. Let 30' of 16" conductor casing in the hole from the surface to 30'.		16" Conductor  7" Casing	0'  115'	30'  844'
<b>Cemented hole from 2193' back to surface as follows:</b> From 2193' to 1297' with 98 sacks of Superlite Cement. From 1297' to 990' with 150 sacks of Supertropic Cement with dye. From 990' to surface with 335 sacks of Superlite Cement. A total of 779 sacks of cement were used to fill the hole from 2193' back to surface. Cement did circulate at the surface.				
<b>Coal Seams</b>		<b>Description of Monument</b>		
<u>Pittsburgh</u>	<u>(1090' - 1097')</u>	77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

RECEIVED  
Office of Oil & Gas  
JAN 02 2014  
WV Department of Environmental Protection

... and that the work of plugging and filling said well was completed on the 26<sup>th</sup> day of September, 2013

And further deponents saith not.

*Delbert Moore*  
Delbert Moore

*Kevin S. Wright*  
Kevin S. Wright

Sworn to and subscribed before me this 30<sup>th</sup> day of October

*Monica De Felice*  
Notary Public

My commission expires: 2/16/2021



Permit No. 47-049-02272-P  
Well No. 5462

01/10/2014