

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address  
CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE STREET MONONGAH, WV 26554  
Address  
THOMAS LEE SNODGRASS  
Lease or Property Owner  
291 EVANS RUN ROAD MANNINGTON, WV 26582  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE STREET MONONGAH, WV 26554  
Complete Address  
GLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
5460  
Well No.  
SNODGRASS, THOMAS LEE  
Farm

STATE INSPECTOR SUPERVISING PLUGGING *William H. ...*

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 30<sup>th</sup> day of September, 2013 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Cleaned 12 1/4" hole from the surface to 229'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 229' to 1199'. Tagged top of 7" casing at 1199'. Removed 169' of 7" casing from the hole from 1199' to 1368'. Continued to clean 9 7/8" hole from 1199' to 1368'. Reduced hole to 6 1/4". Cleaned 6 1/4" hole through 7" casing from 1368' to 2030'. Left 662' of 7" casing in the hole from 1368' to 2030'. Continue to clean 6 1/4" hole from 2030' to 2179'. Tagged solid plug at 2179'. Cut remaining 7" casing at the following depths: 1930', 1830', 1730', 1630', 1530' and 1444'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 975' to 982'. Left 20' of 16" conductor casing in the hole from the surface to 20'.		16" Conductor  7" Casing	0'  169'	20'  662'
<p><b>Cemented hole from 2179' back to surface as follows:</b> From 2179' to 1182' with 220 sacks of 35/65 Poz Cement. From 1182' to 825' with 160 sacks of Thixotropic Cement with dye. From 825' to the surface with 280 sacks of Econofill Cement. A total of 660 sacks of cement were used to fill the hole from 2179' back to surface. Cement did circulate at the surface.</p>				
Coal Seams		Description of Monument		
Pittsburgh	(975' - 982')	77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

RECEIVED  
Office of Oil & Gas  
JAN 02 2014  
WV Department of  
Environmental Protection

... and that the work of plugging and filling said well was completed on the 21<sup>st</sup> day of October, 2013


And further deponents saith not.

*Delbert Moore*  
Delbert Moore  
*Kevin S. Wright*  
Kevin S. Wright

Sworn to and subscribed before me this 18<sup>th</sup> day of November

*Monica De Felice*  
Notary Public

My commission expires:



Permit No. 47-049-02274-P  
Well No. 5460

01/10/2014