

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
DELBERT R. TRIPLETT
Lease or Property Owner
RR 2 BOX 212 MANNINGTON, WV 26582
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
5238
Well No.
TRIPLETT, DELBERT R.
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]* 3-4-14

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

RALPH HARMAN and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 3rd day of December, 2013 and that the well was plugged in the following manner:

| Sand or Zone Record | Filling Material | Casing/Tubing Size | Casing Pulled | Casing Left In |
|---|------------------|---|---------------|----------------|
| Formation | | | | |
| Cleaned 12 1/4" hole from the surface to 305'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 305' to 884'. Removed junk metal and 94' of loose 7" casing from the hole with extreme difficulty, from 884' to 1092'. Possible small junk metal remains through the Pittsburgh Coal seam from 852' to 858'. Continued to clean 9 7/8" hole from 884' to 1092'. Cleaned 9 7/8" hole through the Pittsburgh coal seam from 852' to 858'. Reduced hole to 6 1/2". Cleaned 6 1/2" hole from 1092' to 1110'. Reduced hole to 3 1/2". Cleaned 3 1/2" hole from 1110' to 1168'. | | 16" Conductor | 0' | 18' |
| <p>Cemented hole from 1168' back to surface as follows: From 1168' to 700' with 170 sacks of Thixotropic Cement with dye. Tagged top of bottom hole plug at 752'. From 752' to the surface with 224 sacks of 35/65 Poz Cement. A total of 394 sacks of cement were used to fill the hole from 1168' back to surface. Cement did circulate at the surface. Left 18' of 16" conductor casing in the hole from the surface to 18'.</p> | | | | |
| Coal Seams | | Description of Monument | | |
| Pittsburgh | (852' - 858') | 7" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level. | | |

RECEIVED
Office of Oil & Gas
MAR 20 2014
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 13th day of January, 2014.

And further deponents saith not.

[Signature]
Ralph Harman


[Signature]
Kevin S. Wright

Sworn to and subscribed before me this 17th day of February 2014

[Signature]
Notary Public

My commission expires:

11/4/23



Permit No. 47-049-02280-P
Well No. 5238

03/28/2014