FORM WR-38 (Affidavit of Plugging) STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

ORIGINAL

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSCLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26554
Address
CONSOLIDATION COAL CO.

CONSOLIDATION COAL CO.
Lease of Property Owner

1 BRIDGE STREET MONONGAH, WV 26582
Address

CONSOLIDATION COAL CO.
Name of Well Operator

1 BRIDGE ST. MONONGAH, WV 26554
Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
5120A
Well No.
BAKER, MARGT A

STATE INSPECTOR SUPERVISING PLUGGING

Bell Haveley Sel

5-5-14

AFFIDAVIT

STATE OF WEST VIRGINIA, County of <u>MONONGALIA</u> ss:

ROGER MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 17th day of March, 2014 and that the well was plugged in the following manner:

	Filling Material	Casing	Casing Pulled	Casing Left in
Formation		Size & Kind		
Cleaned 12 ½* hole from the surface to 217'. Reduced hole to 9 7/8*. Cleaned 9 7/8' hole from 217' to 570'. Reduced hole to 7 7/8'. Cleaned 7 7/8" hole from 570' to 1326'. Cleaned 7 7/8" hole through the Pittsburgh Coal seam from 918' to 925'. Cemented hole from 1326' to the surface as follows: From 1376' to 1125' with Expandable Cement. From 1125' to 818' with 165 sacks of Thixotropic Cement with Green Dye. From 818' to surface with Expandable Cement, A total of 415 sacks of Expandable Cement and 165 sacks of Thixotropic Cement were used to cement the hole from 1326' to the surface. Cement did circulate at the surface. Left 20' of 16" conductor casing in the hole from the surface to 20'.		16" Conductor	0,	20'
			RECEI	VED
		Offi	ce of O	& Gas
			MAY 06	2014
		WV Environ	Depart	ment o
		Environ	mental	Protec
Coal Seams		Description of Monument	L	L
PITTSBURGH	918' to 925'	77" of 7" casing w/company name, well number,		
(Name)		permit number and date cemented stated on 7"		
(Name)		casing. Well marker will be attached to the		
(Name)		cement plug at ground level.		

... And that the work of plugging and filling said well was completed on the 7th day of April, 2014.

And further deponents saith not.

Roger Moore

KUM S. Wight

Kevin S. Wight

Sworn to and subscribed before me this 5th, day of May 2014

Kara Beth Forst

My commission expires: 1/4/23

Permit No. <u>47-49-02290-P</u> Well No. <u>5120A</u>

