STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.

Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address

CONSOLIDATION COAL CO.

Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address

CONSOLIDATION COAL CO.

Lease or Property Owner

1 BRIDGE STREET, MONONGAH, WV 26554

Address

CONSOLIDATION COAL CO.

Name of Well Operator

1 BRIDGE STREET MONONGAH, WV 26554

Complete Address

GLOVER GAP 7.5'

Well Location

MANNINGTON

District

MARION County

5336

Well No.

CONSOLIDATION COAL COMPANY

Farm

STATE INSPECTOR SUPERVISING PLUGGING

5-12-14

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MIKE MITCHELL and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 18th day of April, 2014 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left in	
Formation					
Removed all 2 3/8" tubing from the surface to 14'. Cleaned 12 ¼" hole from the surface to 325'. Reduced hole to 9 7/8".		16" Conductor	0'	18'	
Cleaned 9 7/8" hole from 325' to 1178'. Tagged top of 8 5/8" casing at 1178'. Cleaned inside of 8 5/8" casing with 7 7/8" bit from 1178' to 1359'. Continued cleaning 7 7/8" hole from 1359' to 1390'. Tag solid plug at 1390'. Left 181' of 8 5/8" casing in the hole from 1178' to 1359'. Cut remaining 8 5/8" casing at the following depth: 1263'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 901' to 908'. Cemented hole from 1390' back to surface as follows: From 1390' to 1108' with 73 sacks of Expandable Cement. From 1108' to 801' with 155 sacks of Thixotropic Cement with Dye. From 801' to the surface with 455 sacks of Expandable Cement. A total of 683 sacks of cement were used to fill the hole from 1390' back to surface. Cement did circulate at the surface. Left 18' of 16" conductor casing in the hole from the surface to 18'.		8 5/8" Casing	0,	181'	
		2 3/8" Tubing	14'	0,	
		RECEIVED Office of Oil & Gas			
		Office	of Oil 8	Gac	
			1	1	
		MA'	1 9 201	Ą	
		W De	nartmo	nt of	
		-Envisor	War 11 1 117	ir OI	
		-Environme	ntal Pr	ptection	
Coal Seams		Description of Monument			
<u>Pittsburgh</u>	(901' - 908')	77" of 7" casing w/ company name, well number,			
		permit number and date cemented stated on 7"			
		casing. Well marker will be attached to cement			
		plug at ground level.			

... and that the work of plugging and filling said well was completed on the 1st day of May, 2014

And further deponents saith not.

Mike Mitchell

Kavin & Wright

Sworn to and subscribed before me this 12+4 day of May 2014

Kona Beth Forst

My commission expires: ///4/23

Otherd Seel

Watery Public, State Of West Wirginia Wig-III No. 5336

Kora Both Font
Morth American Drillers LLC
70 Gum Spring Rd
Morgantown WW 25503

My commercian express Newsber 4, 2023