

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address  
CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26554  
Address  
MARK A. & CARRIE A. HENDERSHOT  
Lease or Property Owner  
7017 CARRIAGE LANE FAIRMONT, WV 26554  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE ST. MONONGAH, WV 26554  
Complete Address  
GLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
5062  
Well No.  
HENDERSHOT, MARK A. & CAR  
Farm

STATE INSPECTOR SUPERVISING PLUGGING [Signature] 5-12-14

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

BRETT HOWELL and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 15<sup>th</sup> day of April, 2014 and that the well was plugged in the following manner:

Formation	Filling Material	Casing Size & Kind	Casing Pulled	Casing Left In
Cleaned 12 1/4" hole from the surface to 385'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 385' to 1149'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 746' to 752'. Tagged top of 8 5/8" casing at 1148'. Reduced hole to 6 1/4". Cleaned 6 1/4" hole from 1148' to 1278' inside of 8 5/8" casing. Continue to clean 6 1/4" hole from 1278' to 2005'. Tagged solid plug at 2005'. Left 130' of 8 5/8" casing in the hole from 1148' to 1278'.		16" Conductor  8 5/8" Casing	0'  0'	20'  130'
<u>Cemented hole from 2005' to the surface as follows:</u> From 2005' to 976' with 245 sacks of Expandable Cement. From 976' to 631' with 205 sacks of Thixotropic Cement with Green Dye. From 631' to the surface with 375 sacks of Expandable Cement. Cement did circulate at the surface. Left 20' of 16" conductor casing in the hole from the surface to 20'.				
<b>Coal Seams</b>		<b>Description of Monument</b>		
<u>PITTSBURGH</u>	746' to 752'	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7"		
(Name)		casing. Well marker will be attached to the		
(Name)		cement plug at ground level.		

... And that the work of plugging and filling said well was completed on the 25<sup>th</sup> day of April, 2014.

And further deponents saith not.

[Signature]  
Brett Howell

[Signature]  
Kevin S. Wright

Sworn to and subscribed before me this 12th day of May 2014


[Signature]  
Notary Public

My commission expires: 11/6/13

Permit No. 47-49-02306-P  
Well No. 5062

RECEIVED  
Office of Oil & Gas

MAY 19 2014



WV Department of  
Environmental Protection

05/23/2014