STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL CO.

Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address

JEFFREY H. MICHAEL & RONALD C. MICHAEL Lease or Property Owner PO BOX 221 MANNINGTON, WV 26582 Address CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554

Complete Address GLOVER GAP 7.5' Well Location

MANNINGTON
District
MARION

County <u>5247</u> Well No.

CONSOLIDATION COAL COMPANY

Farm

6D - 15 · K,

STATE INSPECTOR SUPERVISING PLUGGING_addle

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

RUSSELL SMALLWOOD and KEVIN WRIGHT being first duly swom according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 29th day of October, 2014 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In]
Formation			1		†
Cleaned 12 ½" hole from Surface to 448'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 448' to 914'. Cleaned 9 7/8" hole		16" Conductor	0'	18'	-
through the Pittsburgh Coal seam from 848' to 854'. Tagged top of 7" casing at 914'. Reduced hole to 6 ½". Cleaned 6 ½" hole from 914' to 1984'. Tagged solid plug at 1984'. Cemented bottom hole plug from 1984' to 1090' with 140 sacks of Expandable Cement. Removed 150' of 7" casing from 914' to 1064'. Left 748'		7" Casing	150'	748'	
of 7" casing in the hole	from 1084' to 1812'. Cleaned 7 7/8" hole			RECEIV	/ED
from 914' to 1064'. Reduced hole to 6 %". Cleaned 6 %" hole from 1064' to 1090'. Tagged top of the bottom hole plug at 1090'.					and Gas
Cemented hole from top of the bottom hole plug at 1090' back to surface as follows; From 1090' to 748' with 185 sacks of Thixotropic Cement with green dye. From 748' back to the Surface with 365 sacks of Expandable Cement. Cement did circulate at the surface. Left 18'				DEC 17	2014
			WV	Depart	ment of
or 16" Conductor Casil	ng in the hole from Surface to 18'.		Enviro	mental	Protection
Coal Seams		Description of Monument			
<u>Pittsburgh</u>	(848' - 854')	77" of 7" casing w/ company name, well number,			ſ
		permit number and date cemented stated on 7" casing. Well marker will be attached to cement			
		plug at ground level.			1

... and that the work of plugging and filling said well was completed on the 14th day of November, 201

And further deponents saith not.

Russell Smallur !:
Russell Smallwood

N S. Wright
Kevin S. Wright

Sworm to and subscribed before me this & day of December 2014

Notary Public

My commission expires: ///4/23

Official Seal

Notiny Public, Case Of West Wights Wight No. 5247

New Both Forst

Annual Defens LLC

70 Gard Spring Rd

Morgandown W 26505

My commission expires November 4, 2022