FORM WR-38 (Affidavit of Plugging)

## STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

## AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be malled to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. Coal Operator or Owner 1 BRIDGE STREET MONONGAH, WV 26554

Address CONSOLIDATION COAL CO.

Coal Operator or Owner

1 BRIDGE STREET MONONGAH, WV 26554

Address MILDRED H PRICHARD HEIRS (C/O PHIL PRICHARD)

Lease or Property Owner
PO BOX 108 MANNINGTON, WV 26582 Address

CONSOLIDATION COAL CO.

Name of Well Operator 1 BRIDGE STREET MONONGAH, WV 26554

Complete Address MANNINGTON 7.5'

**Well Location** 

MANNINGTON District MARION

County 3362

Well No. PRICHARD, MILDRED H HEIRS

STATE INSPECTOR SUPERVISING PLUGGING

**AFFIDAVIT** 

STATE OF WEST VIRGINIA. County of MONONGALIA 88:

STEVIE GOUDY and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 30th day of October, 2014 and that the well was plugged in the following manner:

Sand or Zone Record		Filling Material	Casing/Tubing Size	Casing Pulled	Casing	]
Formation			Gusting Tubing Size	Fulled	Left in	ļ
Cleaned 12 ½" hole from Surface to 87'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 87' to 934'. Cleaned 9 7/8" hole from 87' to 934'. Cleaned 9 7/8" hole from 87' to 478'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 934' to 935'. Reduced hole to 6 ½". Cleaned 6 ½" hole from 935' to 1692'. Tagged solid plug at 1692'. Left 556' of 7" casing in the hole from 966' to 1522'. Left 20' of 16" conductor casing in the hole from Surface to 20'.  Cemented hole from 1692' back to surface as follows: From 1692' to 678' with 209 sacks of Expandable Cement. From 678' to 371' with 190 sacks of Thixotropic Cement with green dye. From 371' back to the Surface with 234 sacks of Expandable Cement. Cement did circulate at the Surface.			16" Conductor	0'	20'	1
			7*	0,	556'	
				l R	ECEIVI	ED
				Office	of Oil a	nd Gas
				D	C 1720	14
·			WV [	epartm	ent of	
			nvironn	nental F	rotectio	
Coal Seams			Description of Manual			
Pittsburgh	(471	' – 478')	Description of Monument 77° of 7° casing w/ company name, well number, permit number and date cemented stated on 7° casing Well mades will be attention.			
	7		casing. Well marker will be attached to cement			
nel that the work	4 -1	mm = 4 49199	plug at ground level. ed on the 12th day of November, 2014			

And further deponents saith not.

Sworn to and subscribed before me this % day of December 2014

My commission expires: |//4//23

