

LATITUDE 39 35

LONGITUDE 80 22 30



7'5 OGIS topo location

7.5' loc \_\_\_\_\_ 15' loc \_\_\_\_\_  
 \_\_\_\_\_ (calc.) \_\_\_\_\_

Company \_\_\_\_\_

Farm HENRY STRAIGHT 1

Quad GLOVER GAP

County MARION

District MANNINGTON

WELL LOCATION MAP

File No. 30020

Mannington District, Marion County, W. Va.

By Eshenbaugh Oil & Gas Co., G. L. Eshenbaugh, President,  
Mannington, W. Va.

On 79 acres, on Dents Run; surface owned by Charles Sine, R. F. D.  
No. 2, Mannington, W. Va., and minerals by Little Kanawha  
Syndicate, Union Trust Co., Trustee, Pittsburgh, Pa.

Drilled under permit issued to W. D. Eshenbaugh, May 9, 1930,  
no number on permit.

Elevation, 1088' B.

16" conductor, 16'; 10" casing, 126'; 8 1/2", 1267'; 6-5/8", 2039';  
5-3/16", 2956' (pulled).

Coal was encountered at 681-686 and 777-782'.

~~Abandoned~~ reported to Dept. of Mines Jan. 2, 1937.

A gas well - gas sand depleted - now being abandoned.

Well was not shot.

Fresh water at 95-105'; salt water at 1740'.

Record to RCT 2-1-37.

Top. Bottom. Thickness.

Hole full water at 95-105'		
Mapletown (Sewickley) Coal, black, good	681 - 686	5
Pittsburgh Coal, black, good (little water)	777 - 782	5
Big Dunkard Sand, white, firm	1262 - 1376	114
Gas Sand, white, firm	1465 - 1550	85
Sand, white, firm	1560 - 1700	140
Salt Sand (hole full water, 1740')	1710 - 1750	40
Little Lime, white, hard	2024 - 2033	9
Pencil Cave, blue, shelly	2033 - 2037	4
Big Lime, white, hard	2037 - 2099	62
Big Injun Sand, white, loose (gas, 2184-2186' and 2190-96')	2099 - 2234	135
50-Ft. Sand, white, close	2770 - 2800	30
30-Ft. Sand, white, close	2830 - 2855	25
Gordon Sand, white, close (gas, 2960')	2955 - 2972	17
No sand below the Gordon.		
Total depth	3300	

MAR-20