

Company Pittsburgh & W. Va. Gas Co.
 Address Clarksburg, W. Va.
 Farm H. S. Bassett
 Tract Acres Lease No. 12930
 Well (Farm) No. One Serial No. 2446
 Elevation (Spirit Level) 1042 V.A.
 Quadrangel Blacksville S.W. 1.3
 County Marion District Paw Paw
 Engineer Paul W. Cunningham
 Engineer's Registration No.
 File No. D 32/P3 Drawing No.
 Date 10/15/47 Scale 1" - 300'

STATE OF WEST VIRGINIA
 Department of Mines
 OIL AND GAS DIVISION
 Charleston

WELL LOCATION MAP
 File No. MAR-519-A

+ Denotes location of well on U.S. Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

H.S. BASNETT No. 1 (2446) - P.G.H. & W.V.A. GAS CO. - MAR-519-A

296

Farmaw District, Marion County, W. Va.
 By Pittsburgh & W. Va. Gas Co., Clarksburg, W. Va.
 On 20 acres; Blacksville 2/4 L-3.
 Elevation, 1042' F. A.
 Surface owned by Stanley Gompaskey, Grant Town, W. Va., and minerals by
 Ida M. Bennett, Farview, W. Va.
 Drilling commenced Aug. 8, 1911; completed Oct. 20, 1911.
 10" casing, 390' (pulled); 8", 1359'; 6", 1609'; 5", 2573' (pulled).
 Coal was encountered at 355-362'.
 Gas well. Abandonment reported to Dept. of Mines Oct. 13, 1947.
 Record to RPT from Mrs. Griffith Oct. 11, 1948. Old File No. 608.

	Top.	Bottom.
Clay, red, soft	0	10
Slate, black, soft	10	65
Lime, white, hard	65	170
Sand, white, hard	170	200
Slate, soft	200	355
Coal	355	362
Slate, soft	362	395
Lime, white, hard	395	470
Red rock, soft	470	550
Slate, soft	550	640
Lime, white, hard	640	680
Slate, soft	680	850
Sand, white, hard	850	945
Slate, black, soft	945	1090
Sand, white, hard (gas, 1120')	1090	1130
Slate, dark, soft	1130	1185
1st Salt Sand, white, hard	1185	1255
Slate, dark, soft	1255	1280
2nd Salt Sand, white, hard (water, 1310')	1280	1365
Slate, white, soft	1365	1410
Red rock, soft	1410	1537
Little lime, blue, hard	1537	1590
Pencil Gave, black, soft	1590	1595
Big lime, blue, hard (gas, 1710-1808')	1595	1670
Big Injun Sand, black, soft (gas, 1808')	1670	1815
Slate, black, soft	1815	1820
Squaw Sand, white, hard	1820	1840
Slate and shells, white, soft	1840	1920
Sand, white, hard	1920	1975
Slate, white, soft	1975	2150
Sand, white, hard	2150	2175
Slate and shells, white, soft	2175	2240
Sand, white, hard	2240	2455
Red rock and shells, hard and soft	2455	2520
Sand, white, hard	2520	2533
Slate and shells	2533	2550
Sand, light, hard	2550	2585
Slate, dark, soft	2585	2600
4th Sand, white	2600	2625
Slate and shells, white, soft	2625	2749
Sand, white, hard (gas, 2749')	2749	2768
Slate and shells, white, soft	2768	2793
Total depth		2793



608

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

WELL RECORD

"GAS"

Oil or Gas Well (KIND)

Permit No. 519-A

Company Pittsburgh & West Va Gas Company.

Address Clarksburg, West Va.

Farm H. S. Bennett Acres 20

Location (waters) Blacksville S/W. 1-3

Well No. 2446 Elev. 1042' VA

District Paw Paw County Marion

The surface of tract is owned in fee by Stanley Cosmpskoy
Address Grant Town, W. Va.

Mineral rights are owned by Ida M. Bennett
Address Fairview, West. Va.

Drilling commenced August 8th, 1911

Drilling completed October 20th, 1911

Date Shot _____ From _____ To _____

With _____

Open Flow _____ /10ths Water in _____ Inch
_____ /10ths Merc. in _____ Inch

Volume _____ Cu. Ft.

Rock Pressure _____ lbs. _____ hrs.

Oil _____ bbls., 1st 24 hrs.

Fresh water _____ feet _____ feet

Salt water _____ feet _____ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			
10	390'	None	Size of
8 1/4	1359'	1359'	
6 5/8	1609'	1609'	Depth set
5 3/16	2573'	None	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom


CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____

COAL WAS ENCOUNTERED AT 355 FEET 84 INCHES

_____ FEET _____ INCHES _____ FEET _____ INCHES

_____ FEET _____ INCHES _____ FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Clay	Red	Soft	0	10			
Slate	Black	"	10	65			
Lime	White	Hard	65	170			
Sand	"	"	170	200			
Slate		Soft	200	355			
Coal			355	362			
Slate		Soft	362	395			
Lime	White	Hard	395	470			
Red Rock	Red	Soft	470	550			
Slate		"	550	640			
Lime	White	Hard	640	680			
Slate		Soft	680	850			
Sand	White	Hard	850	945			
Slate	Black	Soft	945	1090			
Sand	White	Hard	1090	1130	Gas	1120'	
Slate	Dark	Soft	1130	1185			
lst. Salt Sand	White	Hard	1185	1255			
Slate	Dark	Soft	1255	1280			
2nd. Salt Sand	White	Hard	1280	1365	Water	1310'	
Slate	"	Soft	1365	1410			
Red Rock	Red	"	1410	1537			
Little Lime	Blue	Hard	1537	1590			
Pencil Cave	Black	Soft	1590	1595			
Big Lime	Blue	Hard	1595	1670			
Big Injun	White	"	1670	1815	Gas	1710-1808'	
Slate	Black	Soft	1815	1820			
Squaw Sand	White	Hard	1820	1840			
Slate&Shells	"	Soft	1840	1920			
Sand	"	Hard	1920	1975			
Slate	"	Soft	1975	2150			
Sand	"	Hard	2150	2175			
Slate&Shells	"	Soft	2175	2240			
Sand	"	Hard	2240	2455			
Red Rock&Shells		Hard&Soft	2455	2520			
Sand	White	Hard	2520	2533			
Slate&Shells			2533	2550			
Sand	Light	Hard	2550	2585			
Slate	Dark	Soft	2585	2600			
4th. Sand	White		2600	2625			



Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Slate&Shells	White	Soft	2625	2749	Gas	2749'	
Sand	"	Hard	2749	2763			
Slate&Shells	"	Soft	2763	2793			
Total Depth				2793			

Date October 13th, 1947

PITTSBURGH & WEST VA GAS COMPANY., 19____

APPROVED _____, Owner

By *W. E. M. Martin*
(Title)



Record of Well No. 2446 Located on *H. S. Bosnett* Farm *June 10* 19*11*
Paw Paw District *Marion* County *W. Va.* State
 Division *D* District No. *11* Drilled under well Order *286*
 Rig built by *John Craig* Began *July 28* 19*11* Completed *Aug. 5* 19*11*
 Well drilled by *Michado & Bullets* Began *Aug. 8* 19*11* Completed *Oct 20* 19*11*
 Depth of Well *2793* feet Size of Hole *5 3/8* Producing *Gas*
 Elev: *10426*

CASED WITH			REMARKS
AMOUNT	SIZE	KIND	
<i>16'</i>	<i>13"</i>	<i>Wood</i>	
<i>390'</i>	<i>10"</i>	<i>New Reclaimed</i>	
<i>1359'</i>	<i>8 1/4"</i>	<i>"</i>	
<i>1609'</i>	<i>6 5/8"</i>	<i>"</i>	
<i>2576'</i>	<i>5 3/8"</i>	<i>Old. Rec. 1-8 1/4 x 6 9/8 Larkin D. H. Parker</i>	
<i>1828'</i>	<i>2"</i>	<i>1-6 5/8 x 6 3/8 " " "</i>	

COAL VEINS *Pgh. 355-362.*

FORMATIONS							REMARKS
NAME	TOP	BOTTOM	OIL	GAS	WATER		
<i>Big Lime</i>	<i>1595</i>	<i>1670</i>		<i>1'</i>	<i>1325</i>		
<i>Big Drift</i>	<i>1670</i>	<i>1815</i>		<i>1710</i>			
<i>Appan Sand</i>	<i>1920</i>	<i>1940</i>		<i>1808</i>			
<i>Fifty Foot</i>	<i>2240</i>						
<i>Gordon Strag</i>	<i>2520</i>	<i>2535</i>					
<i>Gordon Sand</i>	<i>2552</i>	<i>2585</i>					
<i>Fourth "</i>	<i>2600</i>	<i>2625</i>					
<i>Fifth "</i>	<i>2749</i>	<i>2768</i>		<i>2751</i>	<i>✓</i>		

*Well plugged
September 1948*

FIRST PRESSURE TEST IN ^{6 3/16} CASING

REMARKS

after shot,

Well shot with 30 qts. in fifth sand. Bottom of shell at 27.59.

Time	lbs.
30 Sec.	7
1 Min.	15
2 "	25
5 "	75
10 "	150
15 "	
30 "	
Rock Pressure	325 " in 12 hrs.
Taken	19
By	

WELL TUBED AND PACKED. *Dec. 9, 1916*

VIZ: *8 1/2 qts. 182.8 ft. 7" Tubing
1-6 3/8 X 3/4 Hook Wall Packer.
6 qts. 131 ft. of anchor.*

*5 1/2
182.8
7/16*

FIRST PRESSURE TEST IN ^{2 1/2} TUBING

REMARKS

Time	lbs.
30 Sec.	7
1 Min.	8
2 "	15
5 "	29
10 "	44
15 "	62
30 "	70
Rock Pressure	116 " in 20 hrs.
Taken	<i>Dec. 9-</i> 1916
By	

MATERIAL FOR THIS WELL RECEIVED FROM FOLLOWING SOURCES:

*Rig timbers \$100.00 Latham & Fox,
1159 ft. Lumber \$324.54
Rig Irons " Kelly, Rig & Reel Co.*