



835

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

MAR-704-A

WELL RECORD

Permit No. ~~Marion-143~~

Oil or Gas Well Gas
(KIND)


Company OWENS-ILLINOIS GLASS CO. - GAS DEPT.
 Address P. O. Box 4158, Charleston 4, W. Va.
 Farm Bungne Toothman Acres 21
 Location (waters) Little Paw Paw Creek
 Well No. 1 (OI Serial No. 48) Elev. 1052.8
 District Paw Paw County Marion
 The surface of tract is owned in fee by _____
 Address _____
 Mineral rights are owned by Nesley & Cora Eddy
RFD #1, Rivesville, W. Va. Address _____
 Drilling commenced 4-4-23
 Drilling completed 7-28-23
 Date Shot 7-12-23 From 1785-1800
 With 40 Gts.
 Open Flow _____ /10ths Water in _____ Inch
 _____ /10ths Merc. in _____ Inch
 Volume 130 M Cu. Ft.
 Rock Pressure 98 lbs. 24 hrs.
 Oil _____ bbls., 1st 24 hrs.
 Fresh water _____ feet _____ feet
 Salt water _____ feet _____ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
18			<u>Anchor</u>
10	<u>409'</u>	<u>409'</u>	Size of _____
8 1/4	<u>983'</u>		<u>2" x 6-5/8"</u>
6%	<u>1608'</u>	<u>1608'</u>	Depth set _____
5 3/16			<u>1647</u>
3			Perf. top _____
2		<u>1831'</u>	Perf. bottom _____
Liners Used			Perf. top _____
			Perf. bottom _____

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____

COAL WAS ENCOUNTERED AT _____ FEET _____ INCHES
 _____ FEET _____ INCHES _____ FEET _____ INCHES
 _____ FEET _____ INCHES _____ FEET _____ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Surface gravel			0	14			
Black Slate			14	20			
Lime			20	50			
Black Lime			50	110			
White Lime			110	150			
Slate			150	160			
Black Lime			160	185			
White Lime			185	233			
Mapletown Coal			233	239			
Slate			239	249			
Lime			249	263			
Black Lime			263	268			
White Lime			268	300			
Black Slate			300	335			
Black Lime			335	352			
Pittsburgh Coal			352	359			
Lime			359	360			
Slate			360	409			
Hard Lime			409	439			
Lime			439	495			
Red Rock			495	500			
Lime			500	575			
Sand			575	600			
Lime			600	645			
Hard Lime			645	700			
Slate			700	725			
Sand			725	795			
Lime			795	800			
Slate			800	835			
Lime			835	930			
Lime & Slate			930	983			
Gas Sand			983	1045			
Black Lime			1045	1100			
Coal			1100	1110			
Sand			1110	1120			
1st Salt Sand			1120	1369			
Black Lime			1369	1420			
Marion Sand			1420	1450			
					Water	1308	Hole full



(Over)
MAY 21 1952

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Lime			1450	1490			
Red Rock & Lime			1490	1585			
Little Lime			1585	1591			
Pencil Cave			1591	1604			
Big Lime			1604	1685			
Injun Sand			1685	1830	Gas	1700	show
Lime Shells			1830	1860	"	1791-96	
Black Lime			1860	1900			
Berea Sand			1900	1960			
Slate & Shells			1960	2020			
Shells			2020	2185			
Gantz Sand			2185	2210			
Slate			2210	2215			
Fifty Foot Sand			2215	2285			
Slate			2285	2300			
Thirty Foot Sand			2300	2370			
Red Rock			2370	2374			
Shells			2374	2400			
Sand			2400	2425			
Slate			2425	2480			
Gordon Stray Sand			2480	2495			
Slate & Shells			2495	2540			
Gordon Sand			2540	2565			
Slate			2565	2595			
Sand			2595	2625			
Slate			2625	2650			
Fourth Sand			2650	2670			
White Slate			2670	2720			
Fifth Sand			2720	2770			
Slate			2770	2861			
Total Depth				2861			
Plugged back at completion to				1831			

Date March 20, 1951

APPROVED OWENS-ILLINOIS GLASS CO. - GAS DEPT. Owner

By A. H. Smith

A. H. Smith (Title) Geologist

MUCKERS TOOTHMAN NO. 1 (48) WELL.

Fausch District, Marion County, W. Va.
 By Owens-Illinois Glass Co., Gas Dept., Box 4198, Charleston, W. Va.
 Abandoned under permit No.A?
 On 21 acres, on Little Fausch Creek.
 Elevation, 1052.8' L.
 Minerals owned by Wesley and Cora Eddy, R. F. D. No. 1, Riverview, W. Va.
 Drilling commenced April 4, 1923; completed July 28, 1923.
 Shot July 12, 1923, at 1785-1800', with 40 qts.
 Volume, 130,000 cu. ft.
 Rock pressure, 98 lbs. in 24 hrs.
 10" casing, 409'; 8 1/2", 983' (pulled); 6 3/4", 1608'; 2" tubing, 1831'.
 Anchor packer, 2 x 6 3/4", set at 1647'.
 Gas well. Record to Dept. of Mines dated March 20, 1951.
 Record to ROT from Mrs. Griffith May 21, 1952. C.F.No.835.

	Top.	Bottom.
Surface, gravel	0	- 14
Black slate	14	- 20
Line	20	- 50
Black line	50	- 110
White line	110	- 150
Slate	150	- 160
Black line	160	- 185
White line	185	- 233
Mapleton (Sowickley) Coal	233	- 239
Slate	239	- 249
Line	249	- 263
Black line	263	- 268
White line	268	- 300
Black slate	300	- 335
Black line	335	- 352
Pittsburgh Coal	352	- 359
Lign	359	- 360
Slate	360	- 409
Hard line	409	- 439
Line	439	- 495
Red rock	495	- 500
Line	500	- 575
Sand	575	- 600
Line	600	- 645
Hard line	645	- 700
Slate	700	- 725
Sand	725	- 795
Line	795	- 800
Slate	800	- 835
Line	835	- 930
lime and slate	930	- 983
One Sand	983	- 1045
Black line	1045	- 1100
Coal	1100	- 1110
Sand	1110	- 1120
1st Salt Sand (water, 1308', hole full)	1120	- 1369
Black line	1369	- 1420
Marion Sand	1420	- 1450

(OVER)

KUCKER TOOTHMAN NO. 1 (48) WELL.

Fayette District, Marion County, W. Va.

By Owens-Illinois Glass Co., Gas Dept., Box 4198, Charleston, W. Va.

Abandoned under permit Mar-.....A7

On 21 acres, on Little Payson Creek.

Elevation, 1052.8' L.

Minerals owned by Wesley and Cora Eddy, R. F. D. No. 1, Rivesville, W. Va.

Drilling commenced April 4, 1923; completed July 28, 1923.

Shot July 12, 1923, at 1785-1800', with 40 qts.

Volume, 130,000 cu. ft.

Rock pressure, 98 lbs. in 24 hrs.

10" casing, 409'; 8 1/2", 983' (pulled); 6 3/4", 1608'; 2" tubing, 1831'.

Anchor packer, 2 x 6 3/4", set at 1647'.

Gas well. Record to Dept. of Mines dated March 20, 1951.

Record to RCF from Mrs. Griffith May 21, 1952. C.F.No.835.

	Top.	Bottom.
Surface, gravel	0	14
Black slate	14	20
Line	20	50
Black line	50	110
White line	110	150
Slate	150	160
Black line	160	185
White line	185	233
Mapleton (Sowickley) Coal	233	239
Slate	239	249
Line	249	263
Black line	263	268
White line	268	300
Black slate	300	335
Black line	335	352
Pittsburgh Coal	352	359
Lign	359	360
Slate	360	409
Hard line	409	439
Line	439	495
Red rock	495	500
Line	500	575
Sand	575	600
Line	600	645
Hard line	645	700
Slate	700	725
Sand	725	795
Line	795	800
Slate	800	835
Line	835	930
lime and slate	930	983
Gas Sand	983	1045
Black line	1045	1100
Coal	1100	1110
Sand	1110	1120
1st Salt Sand (water, 1308', hole full)	1120	1369
Black line	1369	1420
Marion Sand	1420	1450

(OVER)

HUGHES FLOTSMAN NO. 1 (48) WELL (Continued).

	Top.	Bottom.
Lime	1450	- 1490
Red rock and lime	1490	- 1585
Little Lime	1585	- 1591
Pencil Gave	1591	- 1604
Big Lime	1604	- 1685
Big Injun Sand (gas show, 1700')		
(gas, 1791-96')	1685	- 1830
Lime shells	1830	- 1860
Black lime	1860	- 1900
Berea Sand	1900	- 1960
Slate and shells	1960	- 2020
Shells	2020	- 2185
Gantz Sand	2185	- 2210
Slate	2210	- 2215
Fifty-foot Sand	2215	- 2285
Slate	2285	- 2300
Thirty-foot Sand	2300	- 2370
Red rock	2370	- 2374
Shells	2374	- 2400
Sand	2400	- 2425
Slate	2425	- 2480
Gordon Stray Sand	2480	- 2495
Slate and shells	2495	- 2540
Gordon Sand	2540	- 2565
Slate	2565	- 2595
Sand	2595	- 2625
Slate	2625	- 2650
Fourth Sand	2650	- 2670
White slate	2670	- 2720
Fifth Sand	2720	- 2770
Slate	2770	- 2861
Total depth		2861
Plugged back at completion to		1831

