

C. H. KOKS NO. 5 WELL.

70130

Harrington District, Marion County, W. Va.

By Clifton Oil & Gas Co.

A. S. Cunningham, Contractor.

Elevation.....

Rig commenced Jan. 19, 1929; completed Jan. 18, 1931.

Drilling commenced Jan. 19, 1929; completed May 6, 1930.

10" casing, 179' 6"; 8 1/2", 1194'; 6 3/4", 1995'; 5 1/2", 2609'.

Shot May 1, 1930, with 20 qts., in Fourth Sand. Top of shot, 2376'.

Bottom of shot, 2019'. Used time jacks.

Shut Aug. 10, 1930.

Surged 4 1/2 hrs oil and 100-bbl. tank.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

	Top.	Bottom.
Conductor	0	20
Highstown (Hershey) Coal	365	370
Pittsburgh Coal (oil)	666	675
Little Richard Sand	1090	1112
Big Richard Sand	1194	1175
Lot Gas Sand	1275	1310
End Gas Sand	1320	1420
First Salt Sand	1455	1480
Second Salt Sand	1640	1725
Horton Sand	1778	1834
Little line	1904	1912
Fossil Gass	1912	1916
Big line	1916	1970
Big Injun Sand (water, 1972') (gas and oil, 2084-2082', oil)	1970
Snow Sand	2133	2160
North shale	2240	2300
Gass Sand	2475	2475
Fifty-foot Sand	2606	2609
Thirty-foot Sand	2713	2730
Boulder Sand	2773	2786
Gordon Stray Sand	2807	2842
Gordon Sand	2845	2861
Fourth Sand (oil, 2880-2882', gas)	2866	2886
Fifth Sand (gas, 3001' heavy light show)	2930	3000
Total depth (oil)		3095

Remarks: All sand and line between 4th and 5th sands.