



Wm. Koontz No. 1.
Producing gas well.
Plugged (1890?).
Elev. 732.50

Pt. in Creek
 Located S. 73° W.
 23' from Sycamore
 16" in diam. & S. 25° W
 28.5' from 6" sycamore

Company PARRIOTT & HAZLETT (Partnership)
 Address RAYMOND PARRIOTT, MOUNDSVILLE, W. Va.
 Farm MYRTLE MOORE
 Tract 1 Acres 30± Lease No. _____
 Well (Farm) No. 1 Serial No. _____
 Elevation (Spirit Level) 744.5
 Quadrangle CAMERON W
 County MARSHALL District WASHINGTON
 Engineer Gordon W. Sammons
 Engineer's Registration No. 509
 File No. _____ Drawing No. _____
 Date Mar. 25-1941 Scale 1" = 300'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. MARS-116

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. M.R.S. 116

Dry Hole
CASING & TUBING

Cameron Quad.	Raymond W. Parrott, Promoter			
Company	Moundsville, R.D.#1	10	40	40
Address	Myrtle Moore Acres 30	8 1/2	400	400
Farm	Middle Grove Creek	65/8	870	870
Location	1. Elev. 732-50/100 745			
Well No.	Washington Marshall County			
District	Myrtle Moore , Moundsville, W.Va.			
Surface	Coal at 265 to 270			
Mineral	Same			
Commenced	10/10/41			
Completed	7/7/42			
Flow	18/10ths W in 2"			
Volume	210 thousand C.F.			
Rock Pressure	Not taken			
Oil	None			
Fresh Water	40'			
Salt Water	1395'			

Gravel			0	40	
Red Rock	Lt	H	40	45	
Slate	Lt	S	45	60	
Lime	Lt	H	60	110	
Slate	Lt	S	110	125	
Lime	Lt	H	125	180	
✓ Coal Blossom		S	180	185	
Lime	Lt	H	185	220	
Shale	Dk	S	220	222	Gas 220 volume 210 thousand
Lime	Lt	H	222	250	222 blew out, pressure not taken.
Slate	Lt	S	250	265	
+✓ Coal	Dk	S	265	270	Per? +480
Lime Gritty	H		270	300	
Slate	Lt	S	300	330	
Lime	Lt	H	330	350	
Slate	Lt	S	350	375	
Lime Gritty	H		375	385	
Red Rock		S	385	410	
Gritty Lime	Lt	H	410	416	
Slate	Gr	S	416	450	
Lime stone Shell			450	455	
Slate & Shells			455	545	
Red Rock		S	545	550	
Slate & Shells			550	660	
Gritty Lime			660	705	
Black Slate		S	705	715	
Lime	Lt	H	715	720	
Pink Rock		S	720	735	
Slate	Dk	S	735	750	
Slate	Lt	S	750	770	
Pink Rock		S	770	785	
Sand	Lt	S	785	800	R.R.
Slate	Dk	S	800	805	
Lime	H		805	810	
Slate	Dk	S	810	870	
✓ Sand	Lt	M	870	910	
Slate	Dk	S	910	990	
Sand		H	990	1015	Water at 1010' 30 gallon per hour
Slate	Dk	S	1015	1045	
Sand	Lt	H	1045	1075	
Slate	Dk	S	1075	1100	
Broken Lime			1100	1275	
✓ Big Lime	Wh	H	1275	1315	
✓ Big Injun			1315	1417	
Total Depth				1417	Water pay from 1390 to 1415 H.F.W.

1275
745
—
530

1275
60
—
1335
735
—
600