

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

MCELROY COAL COMPANY
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address
MCELROY COAL COMPANY
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address
CHARLES E. ANDERSON
Lease or Property Owner
23 VILLAGE DRIVE WHEELING, WV 26003
Address

MCELROY COAL COMPANY
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Complete Address
CAMERON, WV 7.5'
Well Location
CAMERON
District
MARSHALL
County
M-1574
Well No.
ANDERSON, CHARLES E.
Farm

STATE INSPECTOR SUPERVISING PLUGGING *William D. ...*
AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MARK WILSON and **KEVIN S. WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 25th day of October, 2013 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 12 1/4" hole from the surface to 328'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 328' to 971'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 971' to 1680'. Tagged solid plug at 1680'. Cut 8 5/8" casing at 971'. Removed 94' of 8 5/8" casing from the hole from 876' to 971'. Left 117' of 8 5/8" casing in the hole from 971' to 1088'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 735' to 740'. Left 20' of 16" conductor casing in the hole from the surface to 20'.	16" Casing 8 5/8" Casing	0' 94'	20' 117'	
Cemented hole from 1680' to the surface as follows: From 1680' to 940' with Expandable Cement. From 940' to 635' with 170 sacks of Thixotropic Cement with green dye. From 635' to the surface with Expandable Cement. A total of 490 sacks of Expandable Cement and 170 sacks of Thixotropic Cement were used to cement the hole from 1680' to surface. A total of 660 sacks of both cements were used to cement the hole from 1680' to the surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh	(735' - 740')	77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		

RECEIVED
Office of Oil & Gas
JAN 02 2014
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 8th day of November, 2013


And further deponents saith not.

Mark Wilson
Mark Wilson
Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 14th day of November, 2013

Thomas J. Sullivan
Notary Public

My commission expires: 08/16/14



Permit No. 47-51-00146-P
Well No. M-1574

03/28/2014