

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL COMPANY- OHIO VALLEY OPERATIONS
Coal Operator or Owner
RD 4 BOX 425 MOUNDSVILLE, WV 26041
Address

CONSOLIDATION COAL COMPANY- OHIO VALLEY OPERATIONS
Name of Well Operator
RD 4 BOX 425 MOUNDSVILLE, WV 26041
Complete Address

CONSOLIDATION COAL COMPANY- OHIO VALLEY OPERATIONS
Coal Operator or Owner
RD 4 BOX 425 MOUNDSVILLE, WV 26041
Address

MAJORSVILLE, WV 7.5
Well Location

THOMAS H. & ROSALIE ELLIOT
Lease or Property Owner
RR 4 BOX 267 CAMERON, WV 26033
Address

WEBSTER
District
MARSHALL
County

RAYMOND RIGGLE
Lease or Property Owner
RR 4 BOX 267 CAMERON, WV 26033
Address

SGW-89
Well No.
ELLIOT, THOMAS H. & ROSALIE
Farm

STATE INSPECTOR SUPERVISING PLUGGING _____

RECEIVED
Office of Oil & Gas

AFFIDAVIT

JUL 16 2012

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

ROBERT STEEL and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 4th day of May, 2012 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In
Cleaned 3 3/4" hole through existing 4 1/2" casing from surface to original depth at 1781'. 4 1/2" casing was cemented to surface. Ran cement bond log on 4 1/2" casing to verify casing was cemented. Shot 4 1/2" casing with six (6) shots at each of the following depths: 1680', 1580', 1480', 1380', 1280', 1180', 1080', and 980'. Section milled a 10' window in 4 1/2" casing from: 1765' and 1775'. Cemented bottom hole from 1781' back to 900' with 60 sacks of Expandable Cement with Gas Blocker Additive. Sand cut 4 1/2", 7", 8 5/8" and 10 3/4" casing at the following depths: 853', 803', 753', 703', 655', 653', 651.5', 650', 648.5', 647', 645', and 595'. Sand cut 4 1/2", 7", 8 5/8" and 10 3/4" casings through Pittsburgh Coal (647' - 653'). Cleaned 3 3/4" hole through Pittsburgh Coal from 647' to 653'. 7", 8 5/8", and 10 3/4" casing depths were taken from original well record. Left 20' of 16" conductor pipe in the hole from 20' to surface.	16" Conductor 10 3/4" Casing 8 5/8" Casing 7" Casing 4 1/2" Casing	0' 0' 0' 0' 0'	20' 681' 1261' 1760' 1781'	
Coal Seams	Description of Monument			
<u>PITTSBURGH</u>	<u>647' to 653'</u>	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 21st day of May 2012

And further deponents saith not.


Sworn to and subscribed before me this 4th day of June, 2012

Robert Steel
Robert Steel

Kevin S. Wright
Kevin S. Wright

Jacqueline S. Shriver
Notary Public

My commission expires:
March 18, 2020



Permit No. 47-051-00202-P
Well No. SGW-89

07/20/2012