

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Complete Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

MAJORSVILLE, WV 7.5'
Well Location
WEBSTER
District
MARSHALL
County
SGW-159
Well No.

CHARLES ALBERT WITSBERGER II
Lease or Property Owner
250 DRY RIDGE ROAD CAMERON, WV 26033
Address

CHARLES ALBERT WITSBERGER II
Farm

STATE INSPECTOR SUPERVISING PLUGGING [Signature]

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MARK WILSON and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 17th day of September, 2013 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In
Formation				
Cleaned 3 1/2" hole inside of 4 1/2" casing from the surface to 1918'. Continued to clean 3 1/2" hole to 1960'. Tagged solid plug at 1960'. Left 1918' of 4 1/2" casing in the hole from the surface to 1918' due to casing being bonded. Cut 4 1/2" casing at the following depths: 1784', 1688', 1593', 1497', 1401', 1305', 1208', 1111' and 831'. Perforated 4 1/2" casing with 6 Shots at the following depths: 1900', 1880', 1740', 1650', 1550', 1450', 1350', 1250' and 1150'. Cemented bottom hole as follows: From 1960' to 1043' with 65 sacks of Expandable Cement with Gas Blocker additive. Jet Cut 4 1/2", 7", 8 5/8" and 10 1/2" casing at the following depths: 1004', 950', 804', 855', 806.5', 804.5', 802.5', 800.5', 798.5', 757' and 800'. Jet Cut through the Pittsburgh Coal seam from 800' to 806'.	13 3/8" Casing 10 3/4" Casing 8 5/8" Casing 7" Casing 4 1/2" Casing	0' 0' 0' 0'	68' 826' 1388' 1576' 1918'	
Cemented hole from top of bottom hole plug at 1043' to surface as follows:				
From 1043' to 700' with 40 sacks of Thixotropic Cement with green dye. From 700' to the surface with 45 sacks of Expandable Cement. Cement did circulate at the surface. A total of 150 sacks of cement was used cement the hole from 1854' to the surface.				
Coal Seams		Description of Monument		
Pittsburgh Coal	800' to 806'	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

RECEIVED
Office of Oil & Gas
NOV 12 2013
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 24th day of October, 2013

And further deponents saith not.


Mark Wilson
Mark Wilson

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 31 day of October

Monica DeFelice
Notary Public

My commission expires: 2/16/2021



Permit No. 47-051-00331-P
Well No. SGW-159