

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address
CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address
CHARLES ALBERT WITSBERGER II
Lease or Property Owner
2250 DRY RIDGE ROAD CAMERON, WV 26033
Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Complete Address
MAJORSVILLE, WV 7.6
Well Location
WEBSTER
District
MARSHALL
County
SGW-229
Well No.
CHARLES ALBERT WITSBERGER II
Farm

STATE INSPECTOR SUPERVISING PLUGGING *[Signature]*

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MARK WILSON and **KEVIN WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 3rd day of September, 2013 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Plugs Used Size & Kind	Casing Puffed	Casing Left In
Formation				
	Cleaned inside 4 1/2" casing from the surface to 1885'. Tagged solid plug at 1885'. Left 1885' of 4 1/2" casing in the hole from the surface to 1885' due to being bonded in the hole. Cut 4 1/2" casing at the following depths: 1858', 1808', 1714', 1586', 1491', 1396', 1270', 1143', 1050' and 753'. Perforated casing with Six Shots at the following depths: 1814', 1714', 1620', 1514', 1420', 1320', 1214', 1120' and 1020'. Cemented bottom hole from 1885' to 914' with 65 sacks of Expandable Cement. Jet Cut 4 1/2" casing, 7" casing, 8 5/8" casing and 10 3/4" casing the following depths: 914', 864', 814', 764', 715', 713', 711', 709', 707', 659' and 504'. Jet Cut 4 1/2" casing, 7" casing, 8 5/8" casing and 10 3/4" casing through the Pittsburgh Coal seam from 709' to 714'.	13 3/8" Casing 10 3/4" Casing 8 5/8" Casing 7" Casing 4 1/2" Casing	0' 0' 0' 0' 0'	68' 734' 1348' 1684' 1903'
	<u>Cemented hole from top of bottom hole plug at 914' to surface as follows:</u> From 914' to 609' with 45 sacks of Thixotropic Cement with green dye. From 609' to the surface with 50 sacks of Expandable Cement. Cement did circulate at the surface. A total of 160 sacks of cement was used cement the hole from 1885' to the surface.			
Coal Seams		Description of Monument		
Pittsburgh Coal	709' to 714'	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing .Well marker attached to the cement plug at ground level.		

RECEIVED
Office of Oil & Gas
OCT 30 2013
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 13th day of September, 2013

And further deponents saith not.


[Signature]
Mark Wilson

[Signature]
Kevin S. Wright

Sworn to and subscribed before me this 27 day of Sept.

[Signature]
Notary Public

My commission expires:



Permit No. 47-051-00392-P
Well No. SGW-229

11/01/2013