AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS

Coal Operator or Owner 6126 ENERGY DRIVE MOUNDSVILLE, WV 26041

Address

CONSOLIDATION COAL CO. – OHIO VALLEY OPERATIONS
Coal Operator or Owner

6126 ENERGY DRIVE MOUNDSVILLE, WV 26041

Address CHARLES ALBERT WITSBERGER II

Lease or Property Owner
250 DRY RIDGE ROAD CAMERON, WV 26033

Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26941

Complete Address MAJORSVILLE. WV 7.5'

Well Location

WEBSTER

District MARSHALL

County

SGW-157

Well No. CHARLES ALBERT WITSBERGER II

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MARK WILSON and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 31st day of July, 2014 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing / Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 3 7/8" hole from Surface to 1845'. Left 1845' of 4 ½" casing in the hole from Surface to 1845'. Cut remaining 4 ½" casing at the following depths: 1761' and 1661'. Perforated remaining 4 ½" casing with 6 Shots at the following depths: 1556', 1454', 1352', 1254', 1153', 1055', and 956'. Cemented bottom hole plug from 1845' to 855' with 55 sacks of Expandable Cement. Left 526' of 7" casing in the hole from 1129' to 1655'. Left 978' of 8 5/8" casing in the hole from 151' to 1129'. Left 49' of 10 ¾" casings in the hole from 102' to 151'. Jet cut 4 ½", 7", 8 5/8", and 10 ¾" casings at the following depths: 840', 806', 752', 706', 657', 655', 653', 651', 649', 647', 598', and 547'. Jet cut 4 ½", 7", 8 5/8", and 10 ¾" casings through the Pittsburgh Coal seam from 649' to 655'. Left 102' of 13 3/8" conductor casing in the hole from Surface to 102'.		13 3/8" Casing	0,	102'
		10 3/4" Casing	O,	49'
		8 5/8" Casing	0.	978'
		7" Casing	O.	526'
		4 1/2" Casing	0,	1845'
		O	Rece	ived Oil & Ga
Cemented hole from top of bottom hole plug at 855' to surface as follows;			OCT 0	1
From 855' to 549' with 3 dye. From 549' to the su Cement did circulate at	sacks of Thixotropic Cement with green rface with 50 sacks of Expandable Cement. he surface.			
Coal Seams		Description of Monument		
Pittsburgh Coal	649' to 655'	77" of 7" casing w/ company name, well number,		
(Name)		permit number and date cemented stated on 7"		
Name)		casing .Well marker attached to the cement		
(Name)		plug at ground level.		

... and that the work of plugging and filling said well was completed on the 15th day of August, 2014

And further deponents saith not.

Sworn to and subscribed before me this (2)

day of Uctaber 2014

Notary Public

My commission expires: 1/4/23

c. State Of W

Permit No. 47-051-00415-P Well No. <u>SGW-157</u>