

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Complete Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

MAJORSVILLE, WV 7.5

CHARLES ALBERT WITSBERGER II
Lease or Property Owner
250 DRY RIDGE ROAD, CAMERON, WV 26033
Address

Well Location
WEBSTER
District
MARSHALL
County
SGW-152
Well No.

CHARLES ALBERT WITSBERGER
Farm

STATE INSPECTOR SUPERVISING PLUGGING *William H. Winkler* 3-29-13

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MARK WILSON and **KEVIN WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 21st day of March, 2013 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In
Cleaned 7 7/8" hole from the surface to 925'. Tagged solid plug at 925'. Left 805' of 8 5/8" casing in the hole from the surface to 805'. 8 5/8" casing was bonded. Section milled 20' window in 8 5/8" casing from 706' to 726'. Cut 8 5/8" casing at the following depths: 669', 570', 243' and 145'. Section milled 8 5/8" casing through the Pittsburgh Coal seam from 712' to 719'. Left 10' of 16" conductor casing in the hole from the surface to 10'.		16" Casing	0'	10'
		8 5/8" Casing	0'	805'
<p>RECEIVED Office of Oil & Gas MAY 30 2013 WV Department of Environmental Protection</p>				
Cemented hole from 750' back to surface as follows;				
From 925' to 612' with 175 sacks of Thixotropic Cement with green dye. From 612' to the surface with 110 sacks of Expandable Cement. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh Coal	712' to 719'	77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

... and that the work of plugging and filling said well was completed on the 4th day of April, 2013

And further deponents saith not.


Mark Wilson
Mark Wilson

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 22nd day of April 2013

Thomas J. Sullivan
Notary Public

My commission expires



Permit No. 47-051-00468-P
Well No. SGW-152

05/31/2013