

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Complete Address

CONSOLIDATION COAL CO. - OHIO VALLEY OPERATIONS
Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address
CHARLES ALBERT WITSBERGER II
Lease or Property Owner
250 DRY RIDGE ROAD CAMERON, WV 26033
Address

MAJORSVILLE, WV 7.5'
Well Location
WEBSTER
District
MARSHALL
County
SGW-149
Well No.
CHARLES ALBERT WITSBERGER II
Farm

STATE INSPECTOR SUPERVISING PLUGGING *James T. [Signature]*
AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MARK WILSON and **KEVIN WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 16th day of August, 2014 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing / Tubing Size	Casing Pulled	Casing Left In
Cleaned 4 1/4" hole from Surface to 1789'. Left 1714' of 5 1/2" casing in the hole from Surface to 1714'. Cut remaining 5 1/2" casing at the following depths: 1820', 1503', 1406', 1310', 1218', 1121', 1023', 901', 803', and 706'. Perforated remaining 5 1/2" casing with 6 Shots at the following depths: 999', 899', 798', 748', 698', and 648'. Cemented bottom hole plug from 1789' to 797' with 85 sacks of Expandable Cement and 10 sacks of Thixotropic Cement with green dye. Left 655' of 8 5/8" casing in the hole from Surface to 655'. Jet cut 5 1/2" and 8 5/8" casing at the following depths: 600', 598', 596', 594', 592', 590', 542', and 492'. Jet cut 5 1/2" and 8 5/8" casing through the Pittsburgh Coal seam from 591' to 597'. Left 66' of 13 3/8" conductor casing in the hole from Surface to 66'.		13 3/8" Casing	0'	66'
		8 5/8" Casing	0'	655'
		5 1/2" Casing	0'	1714'
Received Office of Oil & Gas OCT 07 2014				
Cemented hole from top of bottom hole plug at 797' to surface as follows:				
From 797' to 491' with 65 sacks of Thixotropic Cement with green dye. From 491' to the surface with 60 sacks of Expandable Cement. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh Coal	591' to 597'	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing .Well marker attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

... and that the work of plugging and filling said well was completed on the 28th day of August, 2014

And further deponents saith not.

Sworn to and subscribed before me this 6 day of October 2014

Mark Wilson
Mark Wilson

Kevin Wright
Kevin Wright

Kara Beth Forst
Notary Public

My commission expires: 11/4/23

Permit No. 47-051-00471-P
Well No. SGW-149

