## STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

## AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Eagle Natrium, LLC Operator Well No.: Pat Wells #1-R

LOCATION:	Elevation: 631 ft.	_	Quadrangle:	New Mart	insville, WV	
	District: Franklin		County:	Marshall	<del></del>	_
		Feet South o		1 14:-	3.5	<del></del>
	Longitude: 0				20.2	
	Longitude.	reet vvest of	f <u>80</u> Deg.	<u> </u>	22.3 Sec.	
Well Type:	OIL N/A GAS N/A	<u> </u>				
Company	Eagle Natrium,LI		perator N/A		Honos	·
	New Martinsville, WV 2	or Ow	ner		Protection 18	Environments
	11011 11121 11134 118, 444 2		Omorotor AVA		to Inemi	NVV Deparament
Agent	J. Thomas Horan	or Owi	Operator N/A			
Permit Issu				•	\$102 <b>\$</b>	<del>हैं तेवेद -</del>
•					Spo nu	
<b>6</b> 74 <b>7</b> 7			AFFIDAVIT		Oil and Gas	) JO 801110
County of Man	EST VIRGINIA,	0			EINED	OEH CEC
	snell ss:	notte a	0.1			
2 M2	and li and	ST CERLACE	nClin	heipa firet	duly sworn accordi	ine to law days
and say that the	ney are experienced in the	the work of plugging	and filling oil and	gas wells and	were employed by	ing to law depose
won operator,	and barrichated in the	work of plugging a	and filling the abo	ve well say t	hat said work was	s commenced on
the 4th	day of September	, 20 <u>14</u> , and the	well was plugge	d and filled i	in the following man	iner:
TYPE	FROM	то	PIPE RE	MOVED	LE	<del></del> 1
Spot Gel	Approx. 7943'	Approx. 6142'	PIPE REMOVED		LEF N/	
Spot Cement	Approx. 6142	Approx. 5000'	N/A		N/	
Spot Gel	Арргох. 5000'	Approx. 4200'	N/A	\	N/A	
Spot Cement	Approx. 4200'	Approx. 4000°	N/A		N/A	+
Spot Gel	Approx. 4000'	Approx. 1955'	N/A		N/A	1
Spot Cement	Approx. 1955'	Approx. 1855'	N/A		N/A	1
Spot Gel	Approx. 1855'	Approx. 1668'	N/A		N/A (Continued	d next page)
Description	of monument: Metal plac	ue with well name. API	number and comple	etion date		
	completed on the 16th		, 20 <u>14</u> .	and and	that the work of p	lugging and filling
And further	deponents saith not.	_				OFFICIAL SEAL
					Sa. A.	NOTARY PUBLIC STATE OF WEST VIRGINIA
		•				KARENSAPD S
Sworn and s	subscribe before me thi	44 July C	an lamba	1.1		535 South Third Avenue Paden City, West Virginia 26159
Owom and s	ing palote the ful	s A I day of 3	premper,	20 <u>14</u>	J	y Commission Expires Apr. 10, 2016
My commission	expires: April 10,	2016	Kaum	Anr		
	,	9	No.	tary Public	<del></del>	·
Afficiant and desire	ad by the Office of the	A -	Tiles	· -	a 1	2 10/06/2017
Aniuavit review	ed by the Office of Oil a	and Gas:	uccom	<u>e</u>	Title: Oc/4	Gez/w2014
		$\bigcup$				•

Form WR-38 (Continued) Affidavit of Plugging and Filling Well API #47-051-0508 September 2014

TYPE	FROM	TO	PIPE REMOVED	LEFT
Spot Cement	Approx. 1668'	Approx. 1550'	N/A	N/A
Spot Gel	Approx. 1550'	Approx. 698'	N/A	N/A
Spot Cement	Approx. 698'	Approx. 600'	N/A	N/A
Spot Gel	Approx. 600'	Approx. 365'	N/A	N/A
Remove 9-5/8" Casing	280′	Surface	280'	1310′
Perforate 13-3/8" Casing	256′	156′	N/A	N/A
Remove 13-3/8" Casing	80′	Surface	80′	207′
Perforate 16" Casing	50′	50′	N/A	N/A
Spot Cement	365'	Surface	N/A	N/A
Install Monument at Surface			.4,1	

Jam Wellocker, Oil & Cocs hispector