

ORIGINAL

FORM WR-38
(Affidavit of Plugging)

STATE OF WEST VIRGINIA
DEPARTMENT OF ENERGY
OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

MCELROY COAL COMPANY
Coal Operator or Owner
RD #4 BOX 425 MOUNDSVILLE, WV 26041
Address
MCELROY COAL COMPANY
Coal Operator or Owner
RD #4 BOX 425 MOUNDSVILLE, WV 26041
Address
MCELROY COAL COMPANY
Lease or Property Owner
1000 CONSOL ENERGY DRIVE, CANONSBURG, PA 15317
Address

MCELROY COAL COMPANY
Name of Well Operator
RD #4 BOX 425 MOUNDSVILLE, WV 26041
Complete Address
CAMERON, WV-PA 7.5'
Well Location
CAMERON
District
MARSHALL
County
M-1093
Well No.
MCELROY COAL COMPANY
Farm

STATE INSPECTOR SUPERVISING PLUGGING _____

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

MARK WILSON and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 17th day of August, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Removed all 2 3/8" tubing from the surface to 800'. Had extreme difficulty removing 2 3/8" tubing from the surface to 800'. Cleaned 12 1/4" hole from the surface to 870'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 870' to 1286'. Tagged plug at 1286'. Left an unknown amount of 8 5/8" casing in the hole from 870' to an unknown depth. 8 5/8" casing was ripped at the following depths: 1270', 1070', 970', 920' and 870'. Cleaned 12 1/4" hole through the Pittsburgh Coal (793 - 798). Left 130' of 16" conductor pipe in the hole from the surface to 130'. <u>Cemented hole from 1286' to surface as follows:</u> From 1286' to 998' with Expandable Cement. From 998' to 693' with 180 sacks of Thixotropic Cement with green dye. From 693' to surface with Expandable Cement. A total of 500 sacks of Expandable Cement and 180 sacks of Thixotropic Cement were used to fill the hole from 1286' to surface. Cement did circulate at the surface.	16" Conductor	0'	130'	
		8 5/8" Casing	0'	Unknown
		2 3/8" Tubing	800'	0'
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	(793' - 798')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		

RECEIVED
Office of Oil & Gas
NOV 20 2012
WV Department of Environmental Protect

... and that the work of plugging and filling said well was completed on the 11th day of October, 2012

And further deponents saith not.

Mark Wilson
Mark Wilson


Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 5th day of November, 2012

Jacqueline L. Shriver
Notary Public

My commission expires:

March 18, 2020



Permit No. 47-051-01411-P
Well No. M-1093

11/23/2012