

COPY

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

**MCELROY COAL COMPANY**  
Coal Operator or Owner  
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041  
Address

**MCELROY COAL COMPANY**  
Coal Operator or Owner  
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041  
Address

**JACK R. HAMMERS AND PAUL F. HAMMERS**  
Lease or Property Owner  
165 OAKMONT ROAD, WHEELING, WV 26003  
#3 SQUIRE VALLEY, BARBOURSVILLE, WV 25504  
Address

**MCELROY COAL COMPANY**  
Name of Well Operator  
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041  
Complete Address

**CAMERON, WV 7.5'**  
Well Location  
**CAMERON**  
District  
**MARSHALL**  
County  
**M-1693**  
Well No.  
**HAMMERS, JACK R. & PAUL F.**  
Farm

STATE INSPECTOR SUPERVISING PLUGGING

*James T. Wilson*  
\_\_\_\_\_

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

**MARK WILSON** and **KEVIN S. WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 20<sup>th</sup> day of December, 2013 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
<b>Formation</b>				
Cleaned 12 1/2' hole from the surface to 293'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 293' to 1006'. Removed rock and junk casing from 728' to 1006'. Milled 5 1/2" casing and junk metal from 1008' to 1035'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 821' to 829'. Removed 244' of 5 1/2" casing from the hole with extreme difficulty from 791' to 1035'. Left unknown amount of 5 1/2" casing in the hole from 1035' to an unknown depth.		16" Casing 5 1/2" Casing	0' 244'	20' Unknown
<b>Cemented hole from 1035' to the surface as follows:</b> From 1035' to 879' with 140 sacks of Thixotropic Cement with dye. Tagged top of bottom hole plug at 915'. From 915' to 721' with 95 sacks of Thixotropic Cement with dye. From 721' to the surface with 365 sacks of Expandable Cement. A total of 600 sacks of both cements were used to cement the hole from 1035' to the surface. Cement did circulate at the surface.				
<b>Coal Seams</b>		<b>Description of Monument</b>		
<b>Pittsburgh</b>	(821' - 829')	77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		

**RECEIVED**  
Office of Oil & Gas  
MAR 24 2014  
WV Department of  
Environmental Protection

... and that the work of plugging and filling said well was completed on the 31<sup>st</sup> day of January, 2014.

And further deponents saith not.


*Mark Wilson*  
\_\_\_\_\_  
Mark Wilson  
*Kevin S. Wright*  
\_\_\_\_\_  
Kevin S. Wright

Sworn to and subscribed before me this 10<sup>th</sup> day of March 2014

*Kara Beth Forst*  
\_\_\_\_\_  
Notary Public

My commission expires: 11/4/23

Permit No. 47-51-01445-P  
Well No. M-1593



03/28/2014