STATE OF WEST VIRGINIA **DEPARTMENT OF ENERGY** OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO., RIVER OPERATIONS

Coal Operator or Owner

RD. 4 BOX 425 MOUNDSVILLE, WV 26041

Address

CONSOLIDATION COAL CO, RIVER OPERATIONS

Coal Operator or Owner

RD, 4 BOX 425 MOUNDSVILLE, WV 26041

Address

MARK WEST ENERGY PARTNERS

Lease or Property Owner

601 TECHNOLOGY DRIVE CANONSBURG, PA. 15317

Address

CONSOLIDATION COAL CO., RIVER OPERATIONS

Name of Well Operator

RD. 4 BOX 425 MOUNDSVILLE, WV 26041

Complete Address

MAJORSVILLE. WV 7.5

Well Location

WEBSTER

District

MARSHALL

County

25A (MW #2) Well No.

MARK WEST ENERGY PARTNERS

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

MARK WILSON and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 31st day of January, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Plugs Used	Casing Pulled	Casing Left In
Formation		Size & Kind		
Cleaned 3 7/8" hole through existing 4 ½" casing from the surface to 813'. Tagged plug at 813'. Attempted to pull 4 ½" casing from		16" Conductor	0'	Unknown
the hole but no movement was detected at the surface. Run cement bond log from the surface to 332'. Bond log indicated that		10 3/4" Casing	0'	Unknown
the 4 ½" casing was cemented to surface. Left 332' of 4 ½" casing in the hole from the surface to 332'. 4 ½" casing was parted from 220' to 224'. Perforate remaining 4 ½" casing with 6 shots at each of the following depths; 280', 250', 223' and 180'. A total of 24 shots were used to perforate the casing from 280' to 180'. Cleaned 3 7/8" hole through the Pittsburgh Coal (278' – 285'). Left an unknown amount of 10 ¾" casing in the hole from the surface to an unknown depth.		4 ½" Casing	0',	332'
Cemented hole from 813' back to surface as follows: From 813' to surface with 360 sacks of Thixatropic Cement with a Gas Blocker additive and green dye. A total of 360 sacks of cement were use to fill the hole from 813' to surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
Pittsburgh Coal	278' to 285'	2'x2' flat plate with company name, well number		
(Name)		permit number and date cemented stated on flat		
(Name)	plate. The 2'X2' flat plate will be placed on the			
(Name)		well three feet beneath the surface.		

... and that the work of plugging and filling said well was completed on the 7th day of February 2012

And further deponents saith not.

ww

Sworn to and subscribed before me this

day of March 2013

Notary Public

My commission expires:

OFFICIAL SEAL
STATE OF WEST VIRGINIA
NOTARY PUBLIC Jacqueline L. Shriver 12 Rousch Drive Wéstover, WV 26501
My Commission Exp. March 18, 2020

Permit No. 47-051-01490 Vell No. <u>CC-25A</u>