FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective

MCELROY COAL COMPANY Coal Operator or Owner
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041 Address MCELROY COAL COMPANY Coal Operator or Owner 6126 ENERGY DRIVE MOUNDSVILLE, WV 26041 Address
MCELROY COAL COMPANY Lease or Property Owner 6126 ENERGY DRIVE, MOUNDSVILLE, WV 26041 Address

MCELROY COAL COMPANY Name of Well Operator 6126 ENERGY DRIVE MOUNDSVILLE, WV 26041 Complete Address CAMERON, WV 7.5' Well Location **CAMERON** District MARSHALL County M-1547 Well No. MCELROY COAL COMPANY

Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA. County of MONONGALIA ss:

MARK WILSON and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 30th day of November, 2012 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 12 %" hole from the surface to 900'. Reduced hole to 6 %". Cleaned 6 %" hole from 900' to 1041'. Tagged solid plug at 1041'. Cleaned 12 %" hole through the Pittsburgh Coal seam from 725' to		16" Conductor	0,	20'
732'. Left 20' of 16" conductor casing from the surface to 20'.		RE	CEIVE	D
Cemented hole from 1041' to surface as follows; From 1041' to 932' with Expandable Cement. From 932' to 625' with 290 sacks of Thixatropic Cement with green dye. From 625' to surface with Expandable Cement. A total of 385 sacks of Expandable Cement and 290 sacks of Thixatropic Cement were used to cement the hole from 1041' to surface. Cement did circulate at the surface.		Office	of Oil 8	Gas
		FE	B 0 4 20	3
		WV D	epartm	ent of
Coal Seams		Description of Monument		
Pittsburgh	(725' - 732')	77" of 7" casing w/ company name, well number,		
		permit number and date cemented stated on 7"		
		casing. Well marker will be attached to the		
		cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 27th day of December, 2012

And further deponents saith not.

Mark Wilson

Sworn to and subscribed before me this

day of Junuary 201 OFFICIAL SEAL

OFFICIAL SEAL
STATE OF WEST VIRGINIA
NOTARY PUBLIC
Jacqueline L. Striver
12 Rousch Drive
Westover, WY 26501
19 (Commission Exp March 18, 2020

Notary Public

Permit No. 47-51-01561-P

My commission expires:

March 18, 2020

Well No. M-1547