FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOL PENNSYLVANIA COAL CO., LLC.

Coal Operator or Owner

1525 PLEASANT GROVE RD. CLAYSVILLE, PA 15323 1000 CONSOL ENERGY DRIVE CANONSBURG, PA 15317 **Address**

CONSOL PENNSYLVANIA COAL CO., LLC.

Coal Operator or Owner

1525 PLEASANT GROVE RD. CLAYSVILLE, PA 15323 1000 CONSOL ENERGY DRIVE CANONSBURG, PA 15317

Address CONSOL PENNSYLVANIA COAL COMPANY, LLC

Lease or Property Owner

1000 CONSOL ENERGY DRIVE CANONSBURG, PA 15317 Address

Farm

CONSOL PENNSYLVANIA COAL CO., LLC. Name of Well Operator

> Complete Address CAMERON, WV 7.5'

Well Location **CAMERON**

District

MARSHALL

County 5037 Well No.

CONSOL PENNSYLVANIA COAL

1000 CONSOL ENERGY DRIVE CANONSBURG, PA 15317

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

ROBERT STEEL and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consol Pennsylvania Coal Company, LLC. Well Operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 1st day of July, 2013 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left in
Formation				
Cleaned 11" hole from the surface to 938'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 938' to 998'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 991' to 998'. Reduced hole to 7 7/8". Cleaned 7 7/8" hole from 998' to 1611'. Reduced hole to 6 1/4". Cleaned 6 1/4" hole from 1611' to 2218'.		16" Conductor	0'	20'
Cemented hole from 2218' back to 891' as follows: From 2218' to 1198' with 265 sacks of Expandive Cement. From 1198' to 891' with 220 sacks of Thixatropic Cement with green dye. A total of 485 sacks of cement were used to fill the hole from 2218' to 891'.		RECEI	VFD	1
		Office of C		as
		AUG 28	2013	
Remaining well bore was then converted into a De-Gasification hole from 891' to surface.		WV Depar Environmenta	tmen ! Pro	of tection
Coal Seams		Description of Monument		
Pittsburgh	(991' - 998')	77" of 7" casing w/company name, well number,		
		permit number and date cemented stated on 7"		
		casing. Well marker will be attached to the		
	of plugging and filling said well was completed on	cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 24th day of

And further deponents saith not.

My commission expires:

S. Wing Kevin S. Wright

Notary Public

Sworm to and subscribed before me this 19 day of Pu6usf

OFFICIAL SEAL STATE OF WEST VIRGINIA NOTARY PUBLIC MONICA DeFELICE RR 3 Box 170C Grafton, WV 26354 My Commission Expires February 16, 2021

ermit No. <u>47-051-01573-P</u> Well No. 5038