

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

November 18, 2013

WELL WORK PERMIT

Horizontal 6A Well

This permit, API Well Number: 47-5101686, issued to NOBLE ENERGY, INC., is evidence of permission granted to perform the specified well work at the location described on the attached pages and located on the attached plat, subject to the provisions of Chapter 22 of the West Virginia Code of 1931, as amended, and all rules and regulations promulgated thereunder, and to all conditions and provisions outlined in the pages attached hereto. Notification shall be given by the operator to the Oil and Gas Inspector at least 24 hours prior to the construction of roads, locations, and/or pits for any permitted work. In addition, the well operator shall notify the same inspector 24 hours before any actual well work is commenced and prior to running and cementing casing. Spills or emergency discharges must be promptly reported by the operator to 1-800-642-3074 and to the Oil and Gas inspector.

Please be advised that form WR-35, Well Operators Report of Well Work is to be submitted to this office within 90 days completion of permitted well work, as should form WR-34 Discharge Monitoring Report within 30 days of discharge of pits, if applicable. Failure to abide by all statutory and regulatory provisions governing all duties and operations hereunder may result in suspension or revocation of this permit and, in addition, may result in civil and/or criminal penalties being imposed upon the operators.

In addition to the applicable requirements of this permit, and the statutes and rules governing oil and gas activity in WV, this permit may contain specific conditions which must be followed. Permit conditions are attached to this cover letter.

Per 35CSR-4-5.2.g this permit will expire in two (2) years from the issue date unless permitted well work is commenced. If there are any questions, please feel free to contact me at (304) 926-0499 ext. 1654.

James Martin

Chief

Operator's Well No: SHL25DHS

Farm Name: RUTHERFORD, DAVID

API Well Number: 47-5101686

Permit Type: Horizontal 6A Well

Date Issued: 11/18/2013

PERMIT CONDITIONS

West Virginia Code § 22-6A-8(d) allows the Office of Oil and Gas to place specific conditions upon this permit. Permit conditions have the same effect as law. Failure to adhere to the specified permit conditions may result in enforcement action.

CONDITIONS

- 1. This proposed activity may require permit coverage from the United States Army Corps of Engineers (USACOE). Through this permit, you are hereby being advised to consult with USACOE regarding this proposed activity.
- 2. If the operator encounters an unanticipated void, or an anticipated void at an unanticipated depth, the operator shall notify the inspector within 24 hours. Modifications to the casing program may be necessary to comply with W. Va. Code § 22-6A-5a (12), which requires drilling to a minimum depth of thirty feet below the bottom of the void, and installing a minimum of twenty (20) feet of casing. Under no circumstance should the operator drill more than fifty (50) feet below the bottom of the void or install less than twenty (20) feet of casing below the bottom of the void.
- 3. When compacting fills, each lift before compaction shall not be more than 12 inches in height, and the fill material shall be within plus or minus 2% of the optimum moisture content as determined by the standard proctor density test, ASTM D698, Standard Test Method for Laboratory Compaction Characteristics of Soil Using Standard Effort. Each lift must meet 95 % compaction of the optimum density based on results from the standard proctor density test of the actual soils used in specific engineered fill sites. Each lift shall be tested for compaction, with a minimum of two tests per lift per acre of fill. All test results shall be maintained on site and available for review.
- 4. Operator shall install signage per § 22-6A-8g (6) (B) at all source water locations included in their approved water management plan within 24 hours of water management plan activation.
- 5. Oil and gas water supply wells will be registered with the Office of Oil and Gas and all such wells will be constructed and plugged in accordance with the standards of the Bureau for Public Health set forth in its Legislative rule entitled *Water Well Regulations*, 64 C.S.R. 19. Operator is to contact the Bureau of Public Health regarding permit requirements. In lieu of plugging, the operator may transfer the well to the surface owner upon agreement of the parties. All drinking water wells within fifteen hundred feet of the water supply well shall be flow tested by the operator upon request of the drinking well owner prior to operating the water supply well.
- 6. Pursuant to the requirements pertaining to the sampling of domestic water supply wells/springs the operator shall, no later than thirty (30) days after receipt of analytical data provide a written copy to the Chief and any of the users who may have requested such analyses.
- 7. If any explosion or other accident causing loss of life or serious personal injury occurs in or about a well or well work on a well, the well operator or its contractor shall give notice, stating the particulars of the explosion or accident, to the oil and gas inspector and the Chief, within 24 hours of said accident.
- 8. During the casing and cementing process, in the event cement does not return to the surface, the oil and gas inspector shall be notified within 24 hours.

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

		WELI	LWORKT	EKWIT ATTEICA	51	6	648
1) Well Operator:	Noble	Energy,	Inc	494501907	Marshall	Sandhill	Valley Grove
A comment	-			Operator ID	County	District	Quadrangle
2) Operator's Well	Number:	SHL 25 DH	HS		Well Pad Name	e: SHL 25	
3 Elevation, curren	t ground:	1310'	E	levation, proposed	post-construct	ion: _1	326'
4) Well Type: (a) (Gas		Oil	Undergroun	d Storage		3
	Other						
(b) I		Shallow		Deep			
		Horizontal					
5) Existing Pad? Ye	es or No:	NO	-				
6) Proposed Target Target-Marcellus, Dep		A 42 - 14 1/2		ited Thicknesses ar	nd Associated I	Pressure(s):	
7) Proposed Total V	ertical De	pth: _6	823'				
8) Formation at Tot	al Vertical	Depth:	Marcellus				
9) Proposed Total N	Measured I	Depth:	13,904'	· C			
10) Approximate F	resh Water	Strata Dep	oths:	213', 300'			
11) Method to Dete	rmine Fres	sh Water D	epth:	Offset well data			
12) Approximate Sa	altwater D	epths:	None noted f	or offsets			
13) Approximate C	oal Seam I	Depths:	810', 866'	Pittsburgh			
14) Approximate D	epth to Po	ssible Void	(coal mine	, karst, other):	None antic	ipated, drilling in p	pillar-see mine maps
15) Does proposed adjacent to an a				directly overlying and depth of mine:	Von Chon	maker Mine with	base at appx. 866'
16) Describe propo Drill Horizontal leg - si			W. OD. T. C.	epth to the Marcellus at an on.	estimated total verti	cal depth of appro	ximately 6,823 feet.
If we should encounter an	unanticipated vo	d we will install c	asing at a minimu	m of 50' below the void but no	t more than 100' below	the void, set a baske	at and grout to surface.
17) Describe fractu				il: well. Stage spacing is depend	dent upon engineering	design. Slickwater	fracturing technique will
be utilized on each sta	age using sand	i, water, and cl	nemicals. See	attached list.			
							CEIVED
18) Total area to be	disturbed	, including	roads, stock	cpile area, pits, etc,	(acres):	Office of 34.92 acres	Oil and Gas
19) Area to be distu	irbed for w	ell pad onl	y, less acce	ss road (acres):	11.71 acre	s SEP	1 6 2013
			Andrew Age Age		8-	ZWV, Dej Environme	partment of 3 ntal Protection

20)

51 01686

CASING AND TUBING PROGRAM

ТҮРЕ	Size	New or Used	Grade	Weight per ft.	FOOTAGE: For Drilling	INTERVALS: Left in Well	CEMENT: Fill -up (Cu. Ft.)
Conductor	30"	N	LS	117#	40'	40'	CTS
Fresh Water	20"	N	LS	94#	400'	400'	CTS
Coal	13 3/8"	N	J-55	54.5#	1250'	1250'	CTS
Intermediate	9 5/8"	N	J-55	36#	3260'	3260'	CTS
Production	5 1/2"	N	P110	20#	13,904'	13,904'	TOC 200' above 9.625 shoe
Tubing							
Liners							

WRH 8-27-13

TYPE	Size	Wellbore Diameter	Wall Thickness	Burst Pressure	Cement Type	Cement Yield
Conductor	30"	36"	0.375		Type 1/Class A	1.2
Fresh Water	20"	26"	.438	2110	Type 1/Class A	1.2
Coal	13 3/8"	17 1/2"	.380	2730	Type 1/Class A	1.2
Intermediate	9 5/8"	12 3/8"	.352	3520	Type 1/Class A	1.19
Production	5 1/2"	8 3/4" & 8 1/2"	.361	12,640	Type 1/Class A	1.27
Tubing						
Liners						

PACKERS

Kind:		RECEIVED	
Sizes:		Office of Oil and Ga	S
Depths Set:		SEP 16 2013	

WV Department of Environmental Protection

Page 2 of 3

*Note: Attach additional sheets as needed.

21) Describe centralizer placei	ment for each casing string.	No centralizers will be use	ed with conductor casing. Surface
casing will have bow spring centralizers on first 2 joints	then every third joint to 100' from surface. Intermediate casing will	have bow spring centralizers on first 2 joints th	en every third joint to 100' from surface. Production
string will have a rigid bow	spring every joint to KOP, rigid	bow spring every third	joint from KOP to top of
cement.			
			
22) Describe all cement additi	ves associated with each cement	type. Conduct	or-1.15% CaCl2.
*Surface-15.6 ppg Type	1 +2% XxL, 0.25# Lost Circ 20	% Excess Yield=1.18	3
Intermediate- 15.6 ppg Cla	ass A +0.4% Ret, 0.15% Disp, 0	.2% AntiFoam, 0.125#	/sk Lost circ 30% Excess
Yield=1.19 to surface. Produc	ction- 14.8 ppg class A 25:75:0 Syste	m +2.6% Cement extende	er, 0.7% Fluid Loss additive,
0.45% high temp retarder	, 0.2% friction reducer 15% Ex	cess Yield=1.27 TOC	greater or equal to 200'
above 9.625" shoe.	-		
*Cement Blend for Surface	ce Casing is a WVDEP Appro	ved Blend.	
23) Proposed borehole conditi	oning procedures. Conductor	-The hole is drilled w/air and cas	ing is run on air. Apart from insuring
the hole is clean via air circu	lation at TD, there are no other co	enditioning procedures.	Surface-The hole is drilled
w/air and casing is run on air. Fill with KC	I water once drilled to TD. Once casing is at setti	ng depth, circulate a minimum of on	e hole volume prior to pumping cement.
Coal-The hole is drilled and cased w/ai	ir or on Freshwater based mud. Once casing i	s at setting depth, the hole is filled	d w/KCI water and a minimum of one
hole volume is circulated prior to pum	ping cement. Intermediate-Once surface car	sing is set and cemented, interm	ediate hole is drilled either on air or
or SOBM and filled with KCI water or	nce drilled to TD. Production-The hole is dr	illed with SOBM and once to TD), circulated at maximum allowable
pump rate for at least 6x bottoms	up. Once on bottom with casing, circula	ate a minimum of one hole ve	olume prior to pumping cement.

RECEIVED
Office of Oil and Gas

SEP 162013

WV Department of 3 Environmental Protection 11/22/2013

west virginia department of environmental protection



Water Management Plan: Primary Water Sources



WMP-01547

API/ID Number:

047-051-01686

Operator:

Noble Energy, Inc.

SHL25DHS

Important:

For each proposed primary water source (including source intakes for purchased water sources) identified in your water management plan, and summarized herein, DEP has made an evaluation concerning water availability over the specified date range. DEP's assessment is based on the following considerations:

- •Statistical analysis of historical USGS stream gauge data (transferred to un-gauged locations as necessary);
- •Identification of sensitive aquatic life (endangered species, mussels, etc.);
- Quantification of known existing demands on the water supply (Large Quantity Users);
- · Minimum flows required by the Army Corps of Engineers; and
- · Designated stream uses.

Based on these factors, DEP has provided, for each intake location (and origination point for purchased water), a reference gauge location and discharge flow reading which must be surpassed prior to withdrawals. Additionally, DEP has established a minimum passby flow at the withdrawal location which must also be surpassed prior to withdrawals. These thresholds are considered terms of the permit and are enforceable as such.

DEP is aware that some intake points will be used for mutiple wells and well sites. In these cases, the thresholds set by the Water Management Plan are to be interepreted as total withdrawal limits for each location over the specified date range regardless of how many wells are supported by that intake.

For all purchased water intakes, determinations of water availability are made at the original source intake location. It is the responsibility of the Oil and Gas Operator, not the seller, to cease withdrawal of water from the seller when flows are less than the minimum gauge reading at the stream gauge referenced by the Water Management Plan in order to protect stream uses.

Note that the determinations made herein are based on the best available data, but it is impossible to predict water availability in the future. While the DEP has carefully established these minimum withdrawal thresholds, it remains the operator's responsibility to protect aquatic life at all times. Approval to withdrawal is contingent upon permission from the land owner. It is the responsibility of the operator to secure and maintain permission prior to any withdrawals.

The operator is reminded that 24-48 hours prior to withdrawing (or purchasing) water, DEP must be notified by email at DEP.water.use@wv.gov.

CAPPROVED NOV 1 3 2013

Source Summary

WMP-01547 API Number: 047-051-01686 Operator: Noble Energy, Inc
SHL25DHS

Purchased Water

Source West Virginia American Water - Weston Water Treatme Lewis Owner: West Virginia American

Water

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude:

9/1/2013 9/1/2014 10,817,000 500,000 - -

Regulated Stream? Stonewall Jackson Dam Ref. Gauge ID: 3061000 WEST FORK RIVER AT ENTERPRISE, WV

Max. Pump rate (gpm): Min. Gauge Reading (cfs): 170.57 Min. Passby (cfs)

DEP Comments:

Source Bethlehem Water Department Ohio Owner: Bethlehem Water Department Department

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude:

9/1/2013 9/1/2014 10,817,000 200,000

Regulated Stream? Ohio River Min. Flow Ref. Gauge ID: 99999999 Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm): Min. Gauge Reading (cfs): 6,468.00 Min. Passby (cfs)

DEP Comments: Bethlehem Water Department purchases all its water from the City of Wheeling.

Thresholds are set based on the location of the City of Wheeling's raw water intake.

Source Wellsburg Water Department
 Brooke Owner: Wellsburg Water
 Department

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude:

9/1/2013 9/1/2014 10,817,000 200,000 - -

Regulated Stream? Ohio River Min. Flow Ref. Gauge ID: 9999999 Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm): Min. Gauge Reading (cfs): 6,468.00 Min. Passby (cfs)

DEP Comments: This alluvial groundwater well is, to some extent, under the influence of the Ohio River.

Please adhere to stated minimum flow requirements on the Ohio River for

withdrawals. http://www.erh.noaa.gov/er/ohrfc/flows.shtml

Source Moundsville Water Board Marshall Owner: Moundsville Water Treatment Plant

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude: 9/1/2013 9/1/2014 10,817,000 2,000,000 - -

Regulated Stream? Ohio River Min. Flow Ref. Gauge ID: 9999999 Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm): Min. Gauge Reading (cfs): 6,468.00 Min. Passby (cfs)

DEP Comments: This alluvial groundwater well is, to some extent, under the influence of the Ohio River.

Please adhere to stated minimum flow requirements on the Ohio River for

withdrawals. http://www.erh.noaa.gov/er/ohrfc/flows.shtml

o Source Dean's Water Service Ohio Owner: Dean's Water Service

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude:

9/1/2013 9/1/2014 10,817,000 600,000 -

Regulated Stream? Ohio River Min. Flow Ref. Gauge ID: 9999999 Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm): Min. Gauge Reading (cfs): 6,468.00 Min. Passby (cfs)

DEP Comments:

• Source Wheeling Water Department Ohio Owner: Wheeling Water Department Department

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude:

9/1/2013 9/1/2014 10,817,000 17,500 - -

Regulated Stream? Ohio River Min. Flow Ref. Gauge ID: 99999999 Ohio River Station: Willow Island Lock & Dam

Max. Pump rate (gpm): Min. Gauge Reading (cfs): 6,468.00 Min. Passby (cfs)

DEP Comments: Refer to the specified sation on the National Weather Service's Ohio River forecasts at

the following website: http://www.erh.noaa.gov/ohrfc//flows.shtml

Source Ohio County PSD
Ohio Owner: Ohio county PSD

Start Date End Date Total Volume (gal) Max. daily purchase (gal) Intake Latitude: Intake Longitude:

9/1/2013 9/1/2014 10,817,000 720,000 - -

Regulated Stream? Ohio River Min. Flow Ref. Gauge ID: 9999999 Ohio River Station: Willow Island Lock & Dam


Max. Pump rate (gpm): Min. Gauge Reading (cfs): 6,468.00 Min. Passby (cfs)

DEP Comments: Refer to the specified station on the National Weather Service's Ohio River forecast

website: http://www.erh.noaa.gov/ohrfc//flows.shtml




Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	321.23	(4)	
2	361.67		
3	465.85	19, 1	
4	266.43	÷	
5	273.47	140	1.0
6	137.03	-	1-
7	88.78	9	
8	84.77	9	
9	58.98	-	
10	57.83	-	
11	145.12	-	
12	247.76		7-1



Water	Availability	y Assessment	of Loc	ation

Base Threshold (cfs):	-
Upstream Demand (cfs):	24.32
Downstream Demand (cfs):	0.00
Pump rate (cfs):	
Headwater Safety (cfs):	8.08
Ungauged Stream Safety (cfs):	0.00
Min. Gauge Reading (cfs):	
Passby at Location (cfs):	


"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.




"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

Median Monthly Flow — Threshold

Passby at Location (cfs):





"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

11

12

26,300.00

41,300.00

			30urce De	tall			
3	WMP-0	1547	API/ID Number: 0.	47-051-0168 HS	6 Operator: Noble	Energy, Inc	
☐ Tro	HUC-8 Code: Drainage Area (dangered Species) out Stream? gulated Stream?	5030106 (sq. mi.): 25000	eam?		Source Latitude: - Source Longitude: - Anticipated withdrawal start date: Anticipated withdrawal end date: Total Volume from Source (gal): Max. Pump rate (gpm): Max. Simultane	9/1/20 9/1/20 10,817 eous Trucks:	014
✓ Ga	uged Stream?				Max. Truck pump	rate (gpm)	
Month 1 2 3 4 5	Reference Gaug Drainage Area (sc Median monthly flow (cfs) 45,700.00 49,200.00 65,700.00 56,100.00 38,700.00 24,300.00	99999999 7. mi.) 25,000 Threshold (+ pump	Ohio River Station: Willo D.00 Estimated Available water (cfs)	w Island Loc	Gauge Threshold (cfs)	: 640	58
6 7 8 9 10 11	16,000.00 13,400.00 12,800.00 15,500.00 26,300.00 41,300.00						
8000 6000 4000	0 Flow on the	nis stream is reg	ulated by the Army o		Water Availability Asses Base Threshold (cfs): Upstream Demand (cfs): Downstream Demand (cfs):		ocation
2000	maintain t	he minimum gu	aranteed flow requi	rements.	Headwater Safety (cfs): Ungauged Stream Safety	y (cfs):	0.00

1

2

3

4

5

6

7

◆ Median Monthly Flow ■ Threshold

8

9

10 11

12


Min. Gauge Reading (cfs):

Passby at Location (cfs):

[&]quot;Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.



Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)
1	45,700.00		
2	49,200.00		-
3	65,700.00		
4	56,100.00	U.	
5	38,700.00		
6	24,300.00		
7	16,000.00	¥.	
8	13,400.00	46	
9	12,800.00	*	
10	15,500.00	C\$-1	-
11	26,300.00	-	1.0
12	41,300.00	-	1.




Base Threshold (cfs):	- 3
Upstream Demand (cfs):	0.00
Downstream Demand (cfs):	0.00
Pump rate (cfs):	
Headwater Safety (cfs):	0.00
Ungauged Stream Safety (cfs):	0.00

Passby at Location (cfs):

Water Availability Assessment of Location

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.



"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

0.00

1

2

3

5

6

7

Median Monthly Flow — Threshold

8

9

10

11

12

Ungauged Stream Safety (cfs):

Min. Gauge Reading (cfs): Passby at Location (cfs):

	WMP-0)1547	API/ID Number:	047-051-01686 IL25DHS	Operator:	Noble Ener	gy, Inc
Source II): 28130 Sou		County PSD ounty PSD			Latitude: - ongitude: -	
☐ Tro ✓ Re	HUC-8 Code: Drainage Area (dangered Species) out Stream? gulated Stream? oximate PSD? uged Stream? Reference Gaug	Mussel Str Tier 3? Ohio River M	in. Flow ater Department	Ohio An	M	al end date: Source (gal):	
	Drainage Area (sc			Timov isiana zook a z		reshold (cfs):	6468
Month	Median monthly flow (cfs)	Threshold (+ pump	Estimated Available water (cfs)				
1	45,700.00	7	-				
2	49,200.00	•	19				
3	65,700.00		-				
4	56,100.00						
5	38,700.00		1.9				
6	24,300.00		1.2				
7	16,000.00	* -	15.00				
8	13,400.00	+	13.				
9	12,800.00		1-3				
10	15,500.00		1.2				
11	26,300.00	-					
12	41,300.00	÷	14	-			
	V	/ater Availa	bility Profile		Water Avail	ability Assessmen	t of Location
					Base Thresh	nold (cfs):	
8000	0				Upstream D	emand (cfs):	
6000	0	^	udated by the Au	man Camac of	Downstrean	n Demand (cfs):	
4000			gulated by the Ar to the stated th		Pump rate (cfs):	
4000	maintain t	he minimum	aranteed flow re	equirements.	Headwater !	Safety (cfs):	0.00
2000	0		•			tream Safety (cfs)	
	1 2	3 4 5	6 7 8 9	10 11 12	Min. Gauge	Reading (cfs):	

"Threshold", as depicted in the chart above is meant only to indicate the calculated base threshold at the proposed withdrawal location. This value does not include the proposed pump rate or existing demand on the stream. Refer to the monthly breakdown above for a more complete estimation of water availability by month.

◆ Median Monthly Flow ■ Threshold

Passby at Location (cfs):

west virginia department of environmental protection



Water Management Plan: **Secondary Water Sources**



WMP-01547

API/ID Number

047-051-01686

Operator:

Noble Energy, Inc

SHL25DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Multi-site impoundment

Source ID: 28131 Source Name

SHL #3 Pad Tank Farm

Source start date:

9/1/2013

Source end date:

9/1/2014

Source Lat:

39.971171

Source Long:

-80.556856

County

Total Volume from Source (gal):

Marshall

Max. Daily Purchase (gal)

10,817,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1435

WMP-01547 API/ID Number 047-051-01686 Operator: Noble Energy, Inc

SHL25DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

SHL #4 Pad Tank Farm Source ID: 28132 Source Name

Source start date: Source end date:

9/1/2013 9/1/2014

Source Lat:

39.956739 Source Long: -80.5515

Marshall

Max. Daily Purchase (gal)

Total Volume from Source (gal):

County

10,817,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-1436

Source ID: 28133 Source Name

SHL #1 Centralized Freshwater Impoundment

Source start date:

9/1/2013

Source end date:

9/1/2014

Source Lat:

39.979696

Source Long:

-80.579465

County

Marshall

Max. Daily Purchase (gal)

Total Volume from Source (gal):

10,817,000

DEP Comments:

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-200

WMP-01547 API/ID Number 047-051-01686 Operator: Noble Energy, Inc

SHL25DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 28134 Source Name SHL #2 Centralized Waste Pit Source start date: 9/1/2013
Source end date: 9/1/2014

Source Lat: 39.966973 Source Long: -80.561377 County Marshall

Max. Daily Purchase (gal) Total Volume from Source (gal): 10,817,000

DEP Comments: WV51-WPC-00001

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-201

Source ID: 28135 Source Name SHL #3 Centralized Waste Pit Source start date: 9/1/2013
Source end date: 9/1/2014

Source Lat: 39.974133 Source Long: -80.55527 County Marshall

Max. Daily Purchase (gal)

Total Volume from Source (gal): 10,817,000

DEP Comments: WV51-WPC-00002

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-202

SHL25DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Source ID: 28136 Source Name

SHL #4 Centralized Waste Pit

Source start date:

9/1/2013

Source end date:

9/1/2014

Source Lat:

39.963284

-80.562743 Source Long:

County

Marshall

Max. Daily Purchase (gal)

Total Volume from Source (gal):

10,817,000

DEP Comments:

WV51-WPC-00003

The intake identified above has been defined in a previous water management plan. The thresholds established in that plan govern this water management plan unless otherwise noted.

Reference: WMP-204

Purchased Water

Source ID: 28128 Source Name

Bridgeport Ohio Water Department

Source start date:

9/1/2013

10,817,000

9/1/2014 Source end date:

Source Lat:

40.08348

Source Long:

-80.736488

County

DEP Comments:

200,000 Max. Daily Purchase (gal) Total Volume from Source (gal):

Please ensure that purchases from this source are approved by, and completed in

accordance with, requirements set forth by the State of Ohio Department of

Environmental Protection.

Public Water Provider

WMP-01547 API/ID Number 047-051-01686 Operator: Noble Energy, Inc
SHL25DHS

Important:

For each proposed secondary water source identified in your water management plan (i.e., groundwater well, lake/reservoir, recycled frac water, multi-site impoundment, out-of-state source), DEP makes no estimation of the availability of water. These sources may prove to be unsuitable water supplies. Please review the following notes:

- •For groundwater supply wells, DEP recommends that the operator contact the local health department prior to drilling any new well; and reminds the operator that all drinking water wells within 1,500 feet of a water supply well shall be flow- and quality-tested by the operator at the request of the drinking well owner prior to operation of the water supply well.
- •For each proposed multi-site impoundment water source identified in your water management plan (if applicable), DEP will review the withdrawal limits established in the referenced Water Management Plan for current suitability and provide to the operator these limits for each identified intake. Note that withdrawal limits may be modified as necessary based on changing demands upon that water supply.

Recycled Frac Water

Source ID: 28137 Source Name SHL25 Well Pad Source start date: 9/1/2013 Source end date: 9/1/2014

Source Lat: Source Long: County

Max. Daily Purchase (gal)

Total Volume from Source (gal): 10,817,000

DEP Comments: Sources include, but are not limited to, the SHL25 well pad.

LA HOMA . 1380 ROAD Green Valley Lakes Sand Hill Schi-1. 9144 Pumping Station ROAD × 40.009694, -80.560555 MESTONE-D △1463 MIGGLE SHL25 Lat: 40.000808 ong: -80.553 40.000257, -80.552777 MC Copyright © 2013 National Geographic Society, i-cubed noble energy SHL25 SITE SAFETY PLAN

2,000 Feet

Disclaimer: All data is licensed for use by Noble Energy Inc. use only.

Scale 1" = 1,000'

Projection: NAD_1927_StatePlane_West_Virginia_North_FIPS_4701 Units: Foot US

- SITE WELL LOCATION -

Well Pad B

Well Pad Cente

RECEIVED Office of Oil and Gas SEP 1 62013

WV Department of

1/22/2013

