

COPY

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

MCELROY COAL COMPANY
Coal Operator or Owner
8126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

MCELROY COAL COMPANY
Coal Operator or Owner
8126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Address

VAN AND VICKIE ASTON
Lease or Property Owner
763 BRUSHY RIDGE ROAD, GLEN EASTON, WV 26039
Address

MCELROY COAL COMPANY
Name of Well Operator
6126 ENERGY DRIVE MOUNDSVILLE, WV 26041
Complete Address

GLEN EASTON, WV 7.5'
Well Location

CAMERON
District

MARSHALL
County

M-1750
Well No.

ASTON, VAN I.
Farm

STATE INSPECTOR SUPERVISING PLUGGING

Jana J. Wolke
AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and **KEVIN S. WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 16th day of April, 2014 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 12 1/4" hole from the surface to 569'. Reduced hole to 9 7/8". Cleaned 9 7/8" hole from 569' to 1151'. Tagged top of 8 5/8" casing at 1151'. Reduced hole to 7 7/8" Cleaned 7 7/8" hole from 1151' to 1690'. Reduced hole to 6 1/2". Cleaned 6 1/2" hole from 1690' to 1828'. Tagged solid plug at 1828'. Cleaned 9 7/8" hole through the Pittsburgh Coal seam from 615' to 622'. Left 249' of 8 5/8" casing in the hole from 1151' to 1400'. Cut remaining 8 5/8" casing at the following depths: 1300' and 1200'.		16" Casing 8 5/8" Casing	0' 0'	20' 249'
Cemented hole from 1828' to the surface as follows:				
From 1828' to 822' with 239 sacks of Expandable Cement. From 822' to 515' with 190 sacks of Thixotropic Cement with Green Dye. From 515' to the surface with 341 sacks of Expandable Cement. A total of 770 sacks of both cements were used to cement the hole from 1828' to the surface. Cement did circulate at the surface. Left 20' of 16" conductor casing in the hole from the surface to 20'.				
Coal Seams		Description of Monument		
Pittsburgh	(615' - 622')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		

RECEIVED
Office of Oil and Gas
JUN 18 2014
WV Department of
Environmental Protection

... and that the work of plugging and filling said well was completed on the 2nd day of May, 2014.

And further deponents saith not.

Delbert Moore
Delbert Moore

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 15th day of May 2014

Kara Beth Foster
Notary Public

My commission expires: 11/4/23

Permit No. 47-51-01747-P
Well No. M-1750

