STATE OF WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL OIL & GAS DIVISION

LD DE MADE IN TRIPLICATE, ONE COPY MAÎLED TO THE STATE OF THE S

	Coal Company		Cons	olidation Coal Co	mpany	
	, Morgantown, WV	26505	P.0.	Box 1314, Morgan		26505
Same	ADDRESS		0ctol	per 17,	**************************************	19_7
COAL OPERATOR OR OWNER			WELL AND LOCATION Battelle		CATION	19
Joseph C. Town	ADDRESS					_Distr
Joseph S. Tennant			Monongalia			C our
Fairview, WV	•		Well. N	To*Nancy Joh	nson #1	
	ADDAKES .	•				
STATE INSPECTOR SUPERVISING PLUGGING			Nancy Johnson			Fa
STATE INSPECTOR S	SUPERVISING PLUG	GING	Wj]]j *Wa	iam Blosser, Colf ell 4117B (skidde	ax, WV	. مد رمد
		AFFID	AVIT	eri 4117b (Skidde	u rocation	1).
STATE OF WEST	·]	-			
County of	ongalia	_}} 22:			•	
Larry Yo			n đ _	David Yost	r <u>u</u>	
being first duly swo	orn according to la	aw depose a	ind say th	at they are experie	nced in the	work
plugging and filling well operator, and n	oil and gas wells ar	nd were em	loyed by	Consolidation	Coal Comp	any
well operator, and p was commenced on	the $\frac{1}{\text{day of}}$	October	ging and	filling the above v	vell, that sa	aid wo
and filled in the foll				, 19 79 , and that the	ne well was	plugg
SAND OR ZONE RECORD	FILLIN	G MATERIAL		PLUGS USED		SING
FORKATION .			•	BIZE & KIND	CsG.	c
Cleaned out we	llbore to 1660'	• Ran .4½	" casine		41/3	14
1660 and pumped!	115 sacks Thivi				7-2	14
16601 1 1455	III SUCKS THINT	tropic cem	ent			
om 1660' to 1455	Pulled 205'	of 4½" ca	sing			
om 1660' to 1455 d pumped 550 sack	Pulled 205's of Pozzmix cer	of 4½" ca ment from	sing 1455'	· ·		
om 1660' to 1455 d pumped 550 sack surface. 4½"	Pulled 205' s of Pozzmix cer loat collar and	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½"	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug			
om 1660' to 1455 d pumped 550 sack surface. 4½" t 1425'. Allow	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug	DESCRIPTION		
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1	Pulled 205' s of Pozzmix celloat collar and ed cement to har	of 4½" ca ment from latch dow	sing 1455' n plug		N OF MONUME	
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1	Pulled 205's of Pozzmix cerloat collar and ed cement to har 400'.	of 4½" ca ment from latch dow	sing 1455' n plug	4½" casing stick	k ing 6' ab	ove
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 COAL SEARS Pittsburgh 6	Pulled 205's of Pozzmix cerloat collar and ed cement to har 400'.	of 4½" ca ment from latch dow	sing 1455' n plug	4½" casing stick surface. Plaque	k ing 6' ab	ove asing
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 COAL SEANS Pittsburgh 6 E)	Pulled 205's of Pozzmix cerloat collar and ed cement to har 400'.	of 4½" cament from latch downden and ba	sing 1455' n plug ailed	4½" casing stick surface. Plaque states: Consol Mon: 47-061-058	ing 6' ab e on 4½" c Well No. 36P	ove asing 4117B
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 COAL SEARS Pittsburgh 6	Pulled 205's of Pozzmix celloat collar and ed cement to har 400'.	of 4½" cament from latch downden and ba	sing 1455' n plug ailed	4½" casing stick surface. Plaque states: Consol Mon: 47-061-058	ing 6' ab e on 4½" c Well No. 36P	ove asing 4117B
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 coal sears Pittsburgh of the work of October	pulled 205' s of Pozzmix celloat collar and ed cement to har 400'. oal 1325 - 1331 of plugging and file 79	of 4½" cament from latch downden and ba	sing 1455' n plug ailed	4½" casing stick surface. Plaque states: Consol Mon: 47-061-058	ing 6' ab e on 4½" c Well No. 36P	ove asing 4117B
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 COAL SEANS Pittsburgh 6 E)	pulled 205' s of Pozzmix celloat collar and ed cement to har 400'. oal 1325 - 1331 of plugging and file 79	of 4½" cament from latch downden and ba	sing 1455' n plug ailed	4½" casing stick surface. Plaque states: Consol Mon: 47-061-058	ing 6' ab e on 4½" c Well No. 36P	ove asing 4117B
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 COAL SEANS Pittsburgh of the work of October And further deposits	Pulled 205' s of Pozzmix cer loat collar and ed cement to har 400'. oal 1325 - 1331 of plugging and fil 79 onents saith not.	of 4½" cament from latch downden and ba	sing 1455' n plug ailed vell was c	surface. Plaque states: Consol Mon: 47-061-058 completed on the	king 6' ab e on 4½" c Well No. 36P	ove asing 4117B
om 1660' to 1455 d pumped 550 sack surface. 4½" 1425'. Allow t 4½" casing to 1 COAL SEANS Pittsburgh of the work of October And further deposits	pulled 205' s of Pozzmix celloat collar and ed cement to har 400'. oal 1325 - 1331 of plugging and file 79	of 4½" cament from latch downden and ba	sing 1455' n plug ailed	surface. Plaque states: Consol Mon: 47-061-058 completed on the	king 6' ab e on 4½" c Well No. 36P	ove asing 4117B