STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE IN TRIPLICATE, one copy mailed to the Department, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

Farm name: Evans, Edward Operator Well No.: F2- 569

LOCATION	I: Elevation: District:	1,172' Clay	Quadrangle: County:		sville ingalia	
	Latitude:	2,398	Feet South of			Coo
	Longitude:	3,723	Feet West of	80 Deg. 1	2 Min 30	_ Sec.
Well Type:	OIL X GAS	0,720		<u>00</u> Deg1	<u> 2 IVIII 1 30 </u>	Sec.
Company:	Eastern Associat	ed Coal LLC	_ Coal Operator:	Eastern Ass	sociated Coal L	I.C.
	1044 Miracle Rur		or Owner		e Run Road	
	Fairview, WV 265			Fairview, W		
			Coal Operator			
Agent:	Matthew L. Bonn	ell	_ or Owner			
Permit Issu	ed Date: October					
OT.	ATE OF MEST M		AFFIDAVIT			
	ATE OF WEST VI unty of <u>Monongalia</u>					
			1 -0 -			
X David	16 Chisler	and	x Jeff Sine		heina first	duly sworn
according to	o law depose and	say that they are	experienced in the	work of plug	iging and filling	n oil and das
wells and w	ere employed by	the above named	well operator, and	participated i	n the work of	olugging and
filling the at	pove well, and <u>Ga</u> y	yne Knitowski, Oil	and Gas Inspector	representing	the Director	say that said
work was c	ommenced on the	8th day of Dece	<u>mber,</u> 2015, and th	at the well wa	as plugged and	d filled in the
following ma	anner:				, 00	
TYPE	FROM	ТО	PIPE REM	OVED	LEF	Т
Drilled with	a 12 1/4" cone bit	down to 827'. Dril	led with a 9 7/8" tri-	-cone down to	1.305'.	
Drilled with Ran logs wi	a 12 1/4" cone bit th Century Wirelin	down to 827'. Dril	led with a 9 7/8" tried on the logs the	-cone down to	1,305'. al seam is 810	
Drilled with Ran logs wi well deviate	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal	down to 827'. Dril ne Services. Base seam. Based on	led with a 9 7/8" tried on the logs the the logs, there was	cone down to Pittsburgh coa	1,305'. al seam is 810 the well)'-817'. The
Drilled with Ran logs wi well deviate There is a l	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal pottom hole ceme	down to 827'. Dril ne Services. Base seam. Based on ant plug from 1,30	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th	cone down to Pittsburgh coa no casing in en they set a	1,305'. al seam is 810 the well)'-817'. The
Drilled with Ran logs wi well deviate There is a the from 1,020'	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal pottom hole ceme to 690'. Then from	down to 827'. Drill ne Services. Base seam. Based on ent plug from 1,30 n 690' to surface it	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen	-cone down to Pittsburgh coa no casing in en they set a nent.	o 1,305'. al seam is 810 the well. an expanding o)'-817'. The
Drilled with Ran logs wi well deviate There is a the from 1,020'	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal pottom hole ceme to 690'. Then from	down to 827'. Drill ne Services. Base seam. Based on ent plug from 1,30 n 690' to surface it	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th	-cone down to Pittsburgh coa no casing in en they set a nent.	o 1,305'. al seam is 810 the well. an expanding o)'-817'. The
Drilled with Ran logs wi well deviate There is a l from 1,020' There were	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portl	down to 827'. Dril ne Services. Base seam. Based on int plug from 1,30 n 690' to surface it land and 140 sack	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	-cone down to Pittsburgh coa is no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a l from 1,020' There were	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal bottom hole ceme to 690'. Then from 600 sacks of Portl	down to 827'. Dril ne Services. Base seam. Based on int plug from 1,30 n 690' to surface it land and 140 sack	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a l from 1,020' There were	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal bottom hole ceme to 690'. Then from 600 sacks of Portl	down to 827'. Dril ne Services. Base seam. Based on int plug from 1,30 n 690' to surface it land and 140 sack	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a t from 1,020' There were Description plugging and	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal bottom hole ceme to 690'. Then from 600 sacks of Portloof monument: 4 1 d filling said well w	down to 827'. Dril ne Services. Base seam. Based on nt plug from 1,30 n 690' to surface it land and 140 sack //2" Pipe with meta ras completed on t	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a t from 1,020' There were Description plugging and	a 12 1/4" cone bit th Century Wirelin d 12.9' at the coal bottom hole ceme to 690'. Then from 600 sacks of Portl	down to 827'. Dril ne Services. Base seam. Based on nt plug from 1,30 n 690' to surface it land and 140 sack //2" Pipe with meta ras completed on t	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a t from 1,020' There were Description plugging and	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal bottom hole ceme to 690'. Then from 600 sacks of Portloof monument: 4 1 d filling said well w	down to 827'. Dril ne Services. Base seam. Based on int plug from 1,30 n 690' to surface it land and 140 sack /2" Pipe with metal as completed on the services.	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a last from 1,020' There were Description plugging and	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portloof monument: 4 1 d filling said well w	down to 827'. Drill he Services. Base seam. Based on an the plug from 1,30 hours for 1,30 hours	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a last from 1,020' There were Description plugging and And	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portle of monument: 4 1 d filling said well well with the deponents of mand subscribe learn and subs	down to 827'. Drill he Services. Base seam. Based on an the plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land sack land and 140 sack land	led with a 9 7/8" tried on the logs the the logs, there was 5' up to 1,020'. The was filled with centre of expanding certain plate, API #, and the 21 st day of Dec	cone down to Pittsburgh consists no casing in en they set an ent. The ment used to pure date plugged ember 2015.	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a last from 1,020' There were Description plugging and And	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal bottom hole ceme to 690'. Then from 600 sacks of Portloof monument: 4 1 d filling said well w	down to 827'. Drill he Services. Base seam. Based on an the plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land sack land and 140 sack land	led with a 9 7/8" tri- ed on the logs the the logs, there was 5' up to 1,020'. Th was filled with cen as of expanding cer	cone down to Pittsburgh coa no casing in en they set a nent. nent used to p	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a last from 1,020' There were Description plugging and And	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portle of monument: 4 1 d filling said well well with the deponents of mand subscribe learn and subs	down to 827'. Drill he Services. Base seam. Based on an the plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land sack land and 140 sack land	led with a 9 7/8" tried on the logs the the logs, there was 5' up to 1,020'. The was filled with centre of expanding certain plate, API #, and the 21 st day of Dec	cone down to Pittsburgh consists no casing in en they set an ent. The ment used to pure date plugged ember 2015.	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a last from 1,020' There were Description plugging and And	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portle of monument: 4 1 d filling said well well with the deponents of mand subscribe learn and subs	down to 827'. Drill he Services. Base seam. Based on an the plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land sack land and 140 sack land	led with a 9 7/8" tried on the logs the the logs, there was 5' up to 1,020'. The was filled with centre of expanding certain plate, API #, and the 21 st day of Dec	cone down to Pittsburgh consists no casing in en they set an ent. The ment used to pure date plugged ember 2015.	o 1,305'. al seam is 810 the well. an expanding o	o'-817'. The cement plug
Drilled with Ran logs wi well deviate There is a la from 1,020' There were Description plugging and And Swo My of	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portloof monument: 4 1 d filling said well we further deponents orn and subscribe from and subscribe from mission expired	down to 827'. Drill he Services. Base seam. Based on an and plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land secompleted on the saith not.	led with a 9 7/8" tried on the logs the the logs, there was 5' up to 1,020'. The was filled with centre of expanding certain plate, API #, and the 21 st day of Dec	cone down to Pittsburgh consists no casing in en they set an ent. The ment used to pure date plugged ember 2015.	o 1,305'. al seam is 810 the well. an expanding of the well. and that the well. NOTARY PUBLIC CRYSTAL	o'-817'. The cement plug ork of , 2015 COFFICIAL SEAL J. SPEARS
Drilled with Ran logs wi well deviate There is a la from 1,020' There were Description plugging and And Swo My of	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portle of monument: 4 1 d filling said well well with the deponents of mand subscribe learn and subs	down to 827'. Drill he Services. Base seam. Based on an and plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land secompleted on the saith not.	led with a 9 7/8" tried on the logs the the logs, there was 5' up to 1,020'. The was filled with centre of expanding certain plate, API #, and the 21 st day of Dec	cone down to Pittsburgh consists no casing in en they set an ent. The ment used to pure date plugged ember 2015.	o 1,305'. al seam is 810 the well. an expanding of plug the well. and that the w	o'-817'. The cement plug ork of , 2015 COFFICIAL SEAL J. SPEARS lest Virginia
Drilled with Ran logs wi well deviate There is a la from 1,020' There were Description plugging and And Swo My of	a 12 1/4" cone bit th Century Wirelind 12.9' at the coal pottom hole ceme to 690'. Then from 600 sacks of Portloof monument: 4 1 d filling said well we further deponents orn and subscribe from and subscribe from mission expired	down to 827'. Drill he Services. Base seam. Based on an and plug from 1,30 he 690' to surface it land and 140 sack land and 140 sack land secompleted on the saith not.	led with a 9 7/8" tried on the logs the the logs, there was 5' up to 1,020'. The was filled with centre of expanding certain plate, API #, and the 21 st day of Dec	cone down to Pittsburgh consists no casing in en they set an ent. The ment used to pure date plugged ember 2015.	o 1,305'. al seam is 810 the well. an expanding of plug the well. and that the well. CRYSTAL State of Well of Well of Well.	o'-817'. The cement plug ork of , 2015 COFFICIAL SEAL J. SPEARS