

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax Earl Ray Tomblin, Governor Randy C. Huffman, Cabinet Secretary www.dep.wv.gov

PERMIT MODIFICATION APPROVAL

February 17, 2016

NORTHEAST NATURAL ENERGY LLC 707 VIRGINIA STREET EAST CHARLESTO, WV 25301

Re: Permit Modification Approval for API Number 6101731, Well #: KASSAY 1H

Modified for Shallower Freshwater

Oil and Gas Operator:

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

Please call James Martin at 304-926-0499, extension 1654 if you have any questions.

Sincerely,

Laura L. adkern Gene Smith

Assistant Chief of Permitting

Office of Oil and Gas

API NO. 47- 061 -	01731
OPERATOR WELL	NO. Kassay 1H
Well Pad Name	Kassav

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

1) Well Operate	or: Northea	st Natural Energ	y LLC	494498281	Monongalia	Clay	Blacksville
				Operator ID	County	District	Quadrangle
2) Operator's V	Vell Number	r: Kassay 1H		Well Pad	Name: Kassa	ıy	
3) Farm Name/	Surface Ow	ner: Nehemiah ar	d Patty A.	Kassay Public Road	d Access: Cour	ity Route 25	/3 (Yank Hollow Road)
4) Elevation, cu	ırrent groun	d: 1,534'	El	evation, proposed p	ost-constructio	on: 1534'	
5) Well Type	(a) Gas	<u>X</u>	Oil	Unde	rground Storag	ge	
	Other				· · · · · · · · · · · · · · · · · · ·	·	
	(b)If Gas	-	X	Deep			
0011		-	<u> </u>		110	اد ادا	
6) Existing Pad						2 2 8	2016
Marcellus, 8,), Antic	ipated Thickness ar	nd Expected Pr	essure(s):	
8) Proposed To	tal Vertical	Depth: 8,289		·			
9) Formation at	Total Verti	cal Depth: M	arcellus				
10) Proposed T	otal Measur	ed Depth: 19	,469.57	71			
11) Proposed H	orizontal La	eg Length: 10	,480'				
12) Approxima	te Fresh Wa	iter Strata Dept	hs:	50' , 1,100'			
13) Method to I	Determine F	resh Water De	pths: [Oriller's Log from (Offset Wells		
14) Approxima	te Saltwater	Depths: 1,94	6' , 2,69)6'			
15) Approxima	te Coal Sear	m Depths: 316	3' , 1,09	8'			
16) Approxima	te Depth to	Possible Void	(coal mi	ne, karst, other): 1	VA		
17) Does Propo directly overlyi				ns Yes	No	<u>x</u>	
(a) If Yes, pro	vide Mine l	Info: Name:	-				
		Depth:					
		Seam:	RE	CEIVED of Oil and Gas			
		Owner:	<u> </u>	} 	RECEIVE Office of Circums	D Gas	
			WV Environ	Depuriment of imental Protection	F43 7		
					WV/ Departme	ent of	

Environmental Figrection

API î	NO.	47	Ola	<u> </u>	٥	17	31	_

OPERATOR WELL NO. Kassay 1H
Well Pad Name: Kassay

18)

CASING AND TUBING PROGRAM

TYPE	Size (in)	New or Used	Grade	Weight per ft. (lb/ft)	FOOTAGE: For Drilling (ft)	INTERVALS: Left in Well (ft)	CEMENT: Fill-up (Cu. Ft.)/CTS
Conductor	24"	New	NA	94.71	40'	40'	GTS
Fresh Water	13-3/8"	New	J-55	54.5	1,199'	1,173'	CTS
Coal							
Intermediate	9-5/8"	New	J-55	40	2,780'	2,750'	CTS
Production	5-1/2"	New	P-110	20	19,469'	19,439'	4,484 Cu. Ft.
Tubing	2-7/8"	New	N-80	6.5	NA	8,500'	NA
Liners							

MgK 2/8/2016

ТҮРЕ	Size (in)	Wellbore Diameter (in)	<u>Wall</u> <u>Thickness</u> <u>(in)</u>	Burst Pressure (psi)	Anticipated Max. Internal Pressure (psi)	Cement Type	Cement Yield (cu, ft./k)
Conductor	24"	30"	.375	415		4,500 psi Grout	NA
Fresh Water	13-3/8"	17 1/2"	.38"	2,760	2,000	Class A	1.23
Coal							
Intermediate	9-5/8"	12 1/4"	.395"	3,950	3,000	Class A	1.3
Production	5-1/2"	8 3/4"	.361"	12,530	9,700	50:50 Poz	1.21
Tubing	2-7/8"	NA	.217"	10,570	3,600	NA	NA
Liners							

PACKERS

Kind:		
Sizes:		
Depths Set:		
	RECEIVED Office of Oil and Gas	

FEB 17 ?

WV Department of Environmental ryotection

WW-6B
(10/14)

API NO. 47- 661- 01731

OPERATOR WELL NO. Kassay 1H

Well Pad Name: Kassay

19) Describe	proposed	well work	, including	the drilling	g and pluggin	g back of an	v pilot hole:

Drilling and completion of a horizontal Marcellus well. The well will be drilled on air to an approximate depth of 7,047.99' TVD/MD. The well will then be horizontally drilled on synthetic based mud from the KOP to approximately 8,289' TVD / 19,469.57' MD along a 323 degree azimuth.

20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:

Multi-stage / high-rate slickwater fracture treatment using various size sands as proppant. First stage

will be initiated via pressurization against a burst disc ran in the production casing string or perforated with coiled tubing. Subsequent stages will be perforated with pumped down guns ran on wireline. Individual stages will be isolated with composite frac plugs. Maximum pump rate during any stage will be 110 BPM with a maximum allowable surface pressure of 9,500 PSI. Composite bridge plugs will be set at the end of the last stage to isolate the treated formation.

21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 15.85

22) Area to be disturbed for well pad only, less access road (acres): 13.00

23) Describe centralizer placement for each casing string:

Surface and intermediate casing strings will have bow spring centralizers placed every third joint (~120') from the shoe joint to surface. Production casing will have rigid body centralizers placed at a minimum of every fourth joint (~160') from TD to surface.

24) Describe all cement additives associated with each cement type:

Surface string cement will be a Class A + Max 3% bwoc Calcium Chloride Fresh Water blend. Intermediate string cement will be a Class A Cement + Max 3% bwoc Calcium Chloride + Fresh Water. Production string cement will be (50:50) Poz (Fly Ash):Type I Cement with a gas migration additive.

25) Proposed borehole conditioning procedures:

Surface string will use a 25.0 bbls Gel Pill + LCM + 25 lbs Cello Flake + 20 lbs/bbl Bentonite @ 8.4 ppg & 10 bbls fresh water spacer prior to cement. Intermediate string will use a 25.0 bbls Gel Pill + LCM + 25 lbs Cello Flake + 20 lbs/bbl Bentonite @ 8.4 ppg & 10 bbls fresh water spacer prior to cement. Production string will use a 50.0 bbls SealBond 25 + 1 gal/tbCES/ED + 275 lbs/bbl Barite + 1 gal/bbl SS-2 Spacer @ 13.5 ppg prior to cement.

FEB 17 203

*Note: Attach additional sheets as needed.

WV Department of Environmental Protection

API NO.	lel-01731
OPERATOR WELL NO.	Kassay 1H
Well Pad Name:	Kassay

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS VOLUNTARY STATEMENT OF NO OBJECTION

Instructions to Persons Named on Page WW-6A

The well operator named on page WW-6A is applying for a permit from the State of West Virginia to conduct oil or gas well work. Well work permits are valid for twenty-four (24) months. Please contact the listed well operator and the Office of Oil and Gas if you do not own any interest in the listed surface tract.

Comment and Waiver Provisions

Pursuant to West Virginia Code § 22-6A-11(a), all persons described in subsection (b), section ten of this article may file written comments with the secretary as to the location or construction of the applicant's proposed well work within thirty days after the application is filed with the secretary.

Pursuant to West Virginia Code § 22-6A-8(b) No permit may be issued less than thirty days after the filing date of the application for any well work except plugging or replugging; and no permit for plugging or replugging may be issued less than five days after the filing date of the application except a permit for plugging or replugging a dry hole: *Provided*. That if the applicant certifies that all persons entitled to notice of the application under the provisions of subsection (b), section ten of this article have been served in person or by certified mail, return receipt requested, with a copy of the well work application, including the erosion and sediment control plan, if required, and the well plat, and further files written statements of no objection by all such persons, the secretary may issue the well work permit at any time.

l, <u>Casey V. Saunders</u> , hereby above, and that I have received copies consisting of pages one (1) through well work on the tract of land as follow State: <u>We</u> County: <u>M</u> District:	st Virginia WVSPI onongalia Public	o Persons Name ion for a Well V rediment control	ed on Page Work Permi I plan, if re- asting: orthing:	WW-6A and the associated provi	ents
I further state that I have no objecti issued on those materials, provided North 422,629.730, East 1,804,38 its rights to mine all the coal or a well by CONSOL Mining Company Mining Company LLC's Common	I that Northeast Natural Energy 2.673. This statement does not sec ccept any responsibility for any of LLC mining activity. This Volu	LLC drills the rve as notice to lamage to the atary Stateme	e well on that CONS well or se ent of No	WV North NAD27 coordina SOL Mining Company LLC has urface facilities associated wi	tes of s waived ith the
*Please check the box that applies		FOR EXE	CUTION	BY A NATURAL PERSON	
☐ SURFACE OWNER		C:			
SURFACE OWNER (Road	BECEIVED	Print Name Date): 		
SURFACE OWNER (Impour	ndments/Pits) Office of Oil and Gas				
☑COAL OWNER OR LESSEI		Company	:		LLC
		By		Casey V. Saunders	
⊠COAL OPERATOR	WV Department of Environmental Protection	on Its		Senior Project Engineer	r
□WATER PURVEYOR	Environmental 1133	Signature Date		V. Saunding 2/12/2016	
OPERATOR OF ANY NATU	JRAL GAS STORAGE FIELD	Date		MI 12/2010	

Oil and Gas Privacy Notice:

The Office of Oil and Gas processes your personal information, such as name, address and telephone number, as part of our regulatory duties. Your personal information may be disclosed to other State agencies or third parties in the normal course of business or as needed to comply with statutory or regulatory requirements, including Freedom of Information Act requests. Our office of Privacy Officer at deprivacyofficer@wv.gov.

FEB 17 ? i