

#### west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, S.E. Charleston, WV 25304 (304) 926-0450 fax: (304) 926-0452

Harold D. Ward, Cabinet Secretary www.dep.wv.gov

Wednesday, May 17, 2023 PERMIT MODIFICATION APPROVAL Horizontal 6A / New Drill

NORTHEAST NATURAL ENERGY LLC 707 VIRGINIA STREET EAST STE 1200 CHARLESTON, WV 25301

Re:

Permit Modification Approval for DOLLS RUN 1H

47-061-01914-00-00

Modified the freshwater casing

### NORTHEAST NATURAL ENERGY LLC

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

If there are any questions, please feel free to contact me at (304) 926-0450.

Martin

Operator's Well Number: DOLLS RUN 1H

Farm Name: BRYAN & SIERRA VANNORMAN

U.S. WELL NUMBER: 47-061-01914-00-00

Horizontal 6A New Drill

Date Modification Issued: 5/17/2023

Promoting a healthy environment.

WW-6B (04/15)

API NO. 47	
OPERATOR WELL NO. 1H	
Well Pad Name: Dolls Run	

# STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

1) Well Operator	Northe	ast Natural I	Energy	494498281	Monongalia	Clay	Osage
-, <b>- F</b>				Operator ID	County	District	Quadrangle
2) Operator's We	ll Number	:: <u>1H</u>		Well Pac	l Name: Dolls	Run	<del></del>
3) Farm Name/Su	ırface Ow	ner: Bryan & S	Sierra Vani	Norman Public Roa	d Access: Littl	e Indian C	reek Rd/SR 41
4) Elevation, curi	ent groun	d: <u>1,535</u> '_	E	levation, proposed	post-constructi	ion: 1,521	
5) Well Type (	a) Gas	X	_ Oil _	Unde	erground Stora	ge	<del></del>
(	Other						RECEIVED -
(	b)lf Gas	Shallow	<u>X</u>	Deep			Office Of Oil and Gas
		Horizontal	<u>X</u>				APR 27 J23
6) Existing Pad:					-		VAV Vegentment out Environmental Productio
7) Proposed Targ Marcellus, 8,02			(s), Antio	cipated Thickness a	and Expected P	ressure(s):	
8) Proposed Tota	l Vertical	Depth: 8,07	'4 <b>'</b>				
9) Formation at T	otal Verti	cal Depth: 1	Marcellu	s			
10) Proposed Tot	tal Measur	ed Depth:	25,141'				
11) Proposed Ho	rizontal L	eg Length:	16,610'				
12) Approximate	Fresh Wa	iter Strata De	pths:	50', 890'			
13) Method to De	etermine F	resh Water D	Depths:	offset wells			
14) Approximate	Saltwater	Depths: 2,2	299'				
15) Approximate	Coal Sea	m Depths: 3	99', 890	ı			
16) Approximate	Depth to	Possible Voi	d (coal m	nine, karst, other):	NA	<u>-</u>	
17) Does Propose directly overlying					No	, <u>X</u>	
(a) If Yes, prov	ide Mine I	Info: Name	:				
		Depth	:				<u>-</u>
		Seam:					
		Owne	r:				

Gayne

Digitally signed by Gayne Knitowski Date: 2023.04.18 07:54:32 -04'00'

4706101914

OPERATOR WELL NO. 1H

Well Pad Name: Dolls Run

18)

# CASING AND TUBING PROGRAM

TYPE	Size (in)	New or Used	Grade	Weight per ft. (lb/ft)	FOOTAGE: For Drilling (ft)	INTERVALS: Left in Well (ft)	CEMENT: Fill-up (Cu. Ft.)/CTS
Conductor	24"	New	NA	NA	100	100'	GTS
Fresh Water	13-3/8"	New	J-55	54.5	1,070'	1,040'	CTS
Coal							
Intermediate	9-5/8"	New	J-55	36	2,530'	2,500	CTS
Production	5-1/2"	New	P-110	20	25,141'	25,141'	5,975
Tubing	2-7/8"	New	P-110	6.5	NA		
Liners		I					

Gayne

Gayne Digitally signed by Gayne Knitowski Date: 2023.04.18 07:54:50 -04'00'

TYPE	Size (in)	Wellbore Diameter (in)	Wall Thickness (in)	Burst Pressure (psi)	Anticipated Max. Internal Pressure (psi)	Cement Type	Cement Yield (cu. ft./k)
Conductor	24"	28"	0.375	NA	NA	Type 1	1.18
Fresh Water	13-3/8"	17-1/2"	0.380	2,730	500	Class A or L	1.19
Coal							·
Intermediate	9-5/8"	12-3/8"	0.395	3,520	2,800	Class A or L	1.19
Production	5-1/2"	8-3/4"	0.361	14,360	11,400	50:50 POZ	1.07
Tubing	2-7/8"	NA	0.271	13,870	NA	NA	NA
Liners					_		

# **PACKERS**

Kind:		
Sizes:		
Depths Set:		

WW-6B (10/14) 4706101914

API NO. 47-\_\_\_\_-\_-OPERATOR WELL NO. 1H

Well Pad Name: Dolls Run

19) Describe proposed well work, including the drilling and plugging back of any pilot hole:

Utilize auger rig to set cellar & conductor. The conductor will be grouted with cement to surface.

Mobilize top hole drilling rig. Drill surface section on air. Run surface (freshwater & coal string) casing to desired depth. The surface section will not penetrate sea level. Surface casing will be cemented to surface. Drill intermediate section on air. Run intermediate casing to desired depth. Intermediate casing will be cemented to surface. Drill on air the production section to the start of the curve (KOP). The well will be loaded with synthetic oil base drilling mud (SOBM). Demobilize top hole rig. Mobilize horizontal drilling rig. Finish drilling the production section utilizing MWD surveys and geosteering practices to maintain the wellbore in the Marcellus shale and prevent anti-collision. Production casing will be ran to TD and cement top will be inside the intermediate casing.

20) Describe fracturing/stimulating methods in detail, including anticipated max pressure and max rate:

A cement bond log will determine the top of production casing cement.

The production casing will be pressure tested. The hydraulic fracturing equipment will then open the toe sleeves and begin pumping the first stage. The plug-and-perf method will be used for the remaining stages. The max anticipated pressure during frac is 11,200psi and a max rate of 90bpm. After frac, the drillout rig will drill all plugs out of the well. Land production tubing at desired depth. Then flowback well until ready to turn in line to production facilities.

- 21) Total Area to be disturbed, including roads, stockpile area, pits, etc., (acres): 27.36
- 22) Area to be disturbed for well pad only, less access road (acres): 10.01

23) Describe centralizer placement for each casing string:

Surface: shoe track & every 3rd joint to surface Intermediate: shoe track & every 3rd joint to surface

Production: Rigid bow centralizers at shoe track & every other joint in the lateral to KOP. Bow springs

from KOP to surface every third joint.

24) Describe all cement additives associated with each cement type:

Surface: Class A or L Cement + Max 3% bwoc Calcium Chloride Fresh Water blend.

Intermediate: Class A or L Cement + Max 3% bwoc Calcium Chloride + Fresh Water.

Production: 50:50 Poz (Fly Ash & Class A or L) plus additives such as defoamer, retarder, & fluid loss to

meet well specific requirements

25) Proposed borehole conditioning procedures:

Surface & intermediate on air will utilize high volumetric flow rates of air to ensure the wellbore is clean prior to TOH.

Production section will utilize synthetic oil based drilling mud to properly clean the wellbore. At TD, pump rate and rotation will be maximized and tripping will not begin until shakers flow clean.

Production casing will be circulated prior to cementing to ensure a prepared wellbore for cement.

\*Note: Attach additional sheets as needed.



RECEIVED
Office Of Oil and Gas

APR 27 2023

WV Department of Environmental Protection