

Map No. 3194, 3306
Hope Natural Gas Company
A. J. McFeeters

Section 2, T. 10 N., R. 10 W., S. 10 E.



Thomas
Lentley

S. E.
Bell

1917

Clay District, Monongalia County, W. Va.
 By Hope Natural Gas Co., 445 W. Main St., Clarksburg, W. Va.
 On 160 acres, surface owned by Mabel C. Spragg, Blacksville, W. Va.
 Drilled prior to June 1, 1929.
 Elevation, 1336' L.
 6-5/8" casing, 1954'; 5-3/16", 2185'.
 Coal was encountered at 600-605 and 942-952'.
 Abandonment reported to Dept. of Mines July 11, 1931
 Well was not shot.
 Water not recorded.
 Gas well; now exhausted to extent of not being commercially
 productive.

	Top.	Bottom.
Native coal	600	- 605
Pittsburgh Coal	942	- 952
Little Dunkard Sand	1320	- 1360
Big Dunkard Sand	1460	- 1475
Gas Sand	1715	- 1740
First Salt Sand	1750	- 1790
Second Salt Sand	1838	- 1934
Little Lime	2155	- 2170
Pencil Cave	2170	- 2176
Big Lime	2176	- 2237
Big Injun Sand (gas, 2306-2320')	2237	- 2440
Squaw Sand	2503	- 2529
Gantz Sand	2725	- 2750
50-Ft. Sand	2800	- 2845
30-Ft. Sand	2865	- 2929
Gordon Sand	3165	- 3182
Fourth Sand (show oil, 3211-3213')	3195	- 3233
Fifth Sand (gas, 3350-3354')	3350	- 3359
Total depth		3370

MON-35-A

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

PRELIMINARY DATA SHEET NO. 1

File No. _____ Well No. 2000Rigs Owned, Operated, or Controlled by _____ Company, of 440 West Union St.Geologist, S. W. _____ as the J. L. Holloman _____ Personcontaining 100 _____ acre Location _____Clay Shales, in Stonewall County, West Virginia.The surface of the above tract covered is for by Walter S. Spragueof Martinsburg, S. W. Va. address, and the mineral rights are owned by _____ of _____

_____ of _____

The oil and gas privileges are held under lease by the above named company, and this well is drilled under

permit No. _____ issued by the West Virginia Department of Mines, Oil and Gas Section,

issued prior to June-July, 1900, is _____Elevation of surface at top of well _____ 2000 _____ 2000

The number of feet of the different sand workings used in the well _____

_____ feet _____ in. Wood _____

2000 feet _____ in. _____ 2000 feet _____ in. _____

_____ feet _____ in. _____ feet _____ in. _____

_____ feet _____ in. _____ feet _____ in. _____

_____ paces of _____ in. _____

_____ paces of _____ in. _____

_____ is conglomerated at _____ feet to _____ feet

_____ is conglomerated at _____ feet to _____ feet

Coal was encountered at _____ feet, thickness _____ inches, and at _____

feet, thickness _____ inches, and at _____ feet, thickness _____ inches

Lenses were used as follows: (If any) _____

July 15, 1900 _____

Approved: _____

By W. L. Holloman _____

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(Repealed by Section 2, Chapter 20, Acts 1929)

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

In and operation between work.
 In and operation between work
 In and operation between work
 In and operation between work
 In and operation between work
 In and operation between work
 In and operation between work

Sege Natural Gas Company
 440 East Main St., CHARLESTON, W. Va.
 August 20, 1929
 Well and location
 State
 County
 No. 1224
 A. J. McFarland, Foreman

THIS STATE OF WEST VIRGINIA, I, JAMES H. McFARLAND, Foreman of the above named well, do hereby certify that the above is a true and correct copy of the original as the same appears in the records of the Oil and Gas Section of the Department of Mines of this State.

AFFIDAVIT

STATE OF WEST VIRGINIA,
 County of Mingo

John F. Shahan and Alan Lee Matthews

being that they were according to law sworn and say that they are experienced in the work of plugging and filling of and gas wells and were employed by Sege Natural Gas Company, well known and participated in the work of plugging and filling the above well, and that well was abandoned on the 20th day of August, 1929, and that the well was plugged and filled in the following manner:

There is a well and was plugged. In plugging and filling of wells in this State it is the usual practice to use a cement slurry, which is a mixture of cement and water, and is placed in the well to a depth of 100 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 200 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 300 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 400 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 500 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 600 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 700 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 800 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 900 feet or more, and is allowed to set. The cement slurry is then placed in the well to a depth of 1000 feet or more, and is allowed to set.

Witness my hand and seal of office at the City of Charleston, West Virginia, this 20th day of August, 1929.

and that the work of plugging and filling said well was completed on the 20th day of August, 1929.

And further deponent says that

CC: 1221

John F. Shahan
Alan Lee Matthews
John F. Shahan
Alan Lee Matthews

Done to and subscribed before me this 20th day of August, 1929, at Charleston, West Virginia.

Case 2583