

LATITUDE

39°45'

80°22'30"

LONGITUDE



7'5 OGIS topo location

7.5' loc	$\frac{2.185}{0.97W}$	15' loc	$\frac{2.185}{3.19W}$
		(calc.)	

Company \_\_\_\_\_

Farm \_\_\_\_\_

Elev 1178

Quad Hundred

County Monongahela

District Bathelle

WELL LOCATION MAP

File No. 061-78A

Plot showing West side of W. C. Minter & Sons, of Pittsburg, Penn. to be abandoned on the Mrs. S. B. Cox farm consisting of 175 Acres, in Puttala District, Monongalia County, West Virginia.



Engineer's Certificate

I, the undersigned hereby certify that this map is correct and shows all the information to the best of my knowledge and belief required by the Oil and Gas section of the Mining Laws of West Virginia.

A. H. Headley  
Engineer

Acknowledged before me a Notary public of Monongalia County, West Virginia, this 26th day of May, 1911.  
April 26, 1911

W. C. Minter  
Notary Public

Battelle District, Monongalia County, W. Va.  
 By H. E. Walker and John R. Conklin, Waynesburg, Pa., and  
 W. F. Minter & Sons, 5529 Black St., Pittsburgh, Pa.  
 On 175 acres, surface and mineral rights owned by Mrs. S. R. Cox,  
 223 S. Walnut St., Morgantown, W. Va.

Elevation, 1130' B.

10" casing, 250'; 8 1/4", 1440'; 6-5/8", 2155'.

Anchor packer, 6-5/8 x 2, set at 2930'.

Casing perforated at 2937 and 3115'.

Coal was encountered at 880-887'.

No liner used.

Abandonment reported to Dept. of Mines May 7, 1934.

We purchased this well from the Cleveland-Cameron Co. and  
 this is the only record they had.

Fresh water cased off with 250' of 10" casing; salt water at 1730'.

Very small well; produced a short time, (gas).

	Top.	Bottom.	Thickness.
Pittsburgh Coal, black,	880 -	887	7
Big Dunkard Sand	1440 -	1490	50
Formation not given in well log (gas)	1583 -	1640	57
1st Salt Sand (water, 1730')	1665 -	1790	125
Red rock, slate	2010 -	2020	10
Big Lime, white	2080 -	2155	75
Big Injun Sand	2155 -	2390	235
50-Ft. Sand	2850 -	2870	20
30-Ft. Sand	2895 -	2920	25
Stray Sand (gas, 2937'p packer, 2930')	2923 -	2960	37
Gordon Sand	2975 -	3002	27
Fourth Sand	3025 -	3080	55
Fifth Sand (gas, 3115')	3110 -	3135	25
Total depth		3363	

## WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS INTENSIVE

## PRELIMINARY DATA SHEET NO. 1

E. E. Walker  
 John E. Goshlin  
 GEORGETOWN, PENN. &

Well No. 11

E. F. Sinton & Sons Company of 2047 Black St.

Georgetown, Penn. on the MRS. E. S. Cox Street

Section 130 Area Location

Bedford, Ohio, in Morganlia County, West Virginia

The surface of the strata to be covered is the MRS. E. S. Cox

MRS. E. S. Cox, Morgantown, W. Va. address, and the mineral rights reserved by

Mrs. E. S. Cox of Morgantown, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

issued by the West Virginia Department of Mines, Oil and Gas Intensive

Section

Thickness of surface at top of well, 1180' Open

The number of feet of the different steel casings used in the well.

Size	Length	Weight	Material
8 1/2"	10'	also, 100'	Welded steel
10"	21'	also, 100'	steel pipe
12 1/2"	6 5/8'	also, 100'	steel pipe
14"	6 5/8' by 3'	also, 100'	steel pipe

Another 6 5/8' by 3' also, 100'

is casing perforated at 2047 E. at 2115 feet to

is casing perforated at

that was connected at 200 feet, distance 7 ft. below, and at

any distance below and at

distance was used as follows (give details) 2000

2000

2000

2000

2000

2000

2000

2000

2000

2000

2000

2000

2000

2000

Page 1 of 1

Date

Approved: E. F. Sinton & Sons

By: *E. F. Sinton*

H. E. SALKER,  
John E. Conklin of Waynesburg, Penna.  
& W. F. Minter & Sons

Company

5529 Black St., Pittsburgh, Pa.

Well No. 1

COMPLETION DATA SHEET  
NO. 2  
FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Pgh. Coal	Black	Coal		890	887	3'		
Big Dunkard		Sand		1440	1490	50'		
Formation	not given	in well log	Gas	1583	1640	57'		
1st Salt		Sand		1645	1790	145'		
Red Rock	Red	Slate	Water 1730	2010	2020	10'		
Big Lime	White	Lime		2090	2155	65'		
Big Injun		Sand		2155	2290	135'		
Fifty Ft.		Sand		2290	2370	80'		
Thirty Ft.		Sand		2370	2390	20'		
Stray		Sand		2390	2420	30'		
Gordon		Sand	Gas 2927	2923	2960	37'		
Fourth		Sand		2975	3005	30'		
Fifth		Sand		3025	3090	65'		
Total Depth		Sand	Gas 3115	3110	3135	25'	3365	

No purchased this well from the Cleveland-Cameron Co.  
and this is the only record they had.

5/19/24

Well was not shot at. Shot well was shot at.  
Cased off with 250' Fresh water and 12" casing. Shot well water at 1730'.  
Very small well, produced a short time.

May 7, 1924

Approved: W. F. Minter & Sons,

*W. F. Minter, Partner*

NOTE: All bottom descriptions must be noted as indicated above and all top-cuts and oil and gas sands must be recorded under their proper geological names in the column as well as any local culture commonly used in the district for each stratum.