



THESE LOTS ARE THE PROPERTY OF THE STATE OF TEXAS AND ARE BEING OFFERED FOR SALE BY THE COMMISSIONER OF THE GENERAL LAND OFFICE. THE BOUNDARIES SHOWN ON THIS MAP ARE THE RESULT OF A SURVEY MADE BY THE COMMISSIONER OF THE GENERAL LAND OFFICE IN 1854.

*James F. [Signature]*  
*W. M. [Signature]*

LATITUDE 39°42'30"

9390

7.5'



88°20'00"

LONGITUDE

7.5 OGIS topo location

7.5' loc	<u>0.525</u>	15' loc	<u>3.405</u>
	<u>0.950</u>	(calc.)	<u>0.950</u>

5063 on Equitrans

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad Wadestown (Mannington NC)

County Monongahela

District Battelle

WELL LOCATION MAP

File No. 0161-106A

Battelle District, Monongalia County, W. Va.  
 By Arthur Mackey, Wadestown, W. Va.  
 On 136 acres, surface owned by Frank Liming, Wadestown, W. Va.  
 Elevation, 1345' L.  
 6-5/8" casing, 2028'; 5-3/16", 2337'.  
 Coal was encountered at 754-759, 1013-1021, and 1095-1103'.  
 No liner used.  
 Abandonment reported to Dept. of Mines March 11, 1935.  
 (Pittsburgh & W. Va. Gas Co. well).  
 Well was not shot.  
 Producing hole.

MON-106-A

	Top.	Bottom.
Fairview (Waynesburg) Coal	754	- 759
Mapletown (Sewickley) Coal	1013	- 1021
Pittsburgh Coal	1095	- 1103
Little Dunkard Sand	1506	- 1540
Big Dunkard Sand	1590	- 1640
Gas Sand	1785	- 1860
First Salt Sand	1918	- 1960
Second Salt Sand	1970	- 2060
Red rock	2130	- 2150
Little Lime	2262	- 2292
Big Lime	2330	- 2388
Big Injun Sand	2388	- 2600
Gantz Sand	2900	- 2945
50-Ft. Sand	3045	- 3161
Gordon Stray	3191	- 3207
Gordon Sand	3209	- 3233
Fourth Sand	3239	- 3309
Fifth Sand	3324	- 3408
Total depth		3521

Farm \_\_\_\_\_

Quad Wadestown (Monongalia No)

County Monongahela

District Battelle

WELL LOCATION MAP

File No. 0161-106A

# WEST VIRGINIA DEPARTMENT OF MINES

## OIL AND GAS DIVISION

### PRELIMINARY DATA SHEET NO. 1

File No. \_\_\_\_\_

Well No. 5063

Arthur Jambry Company of Madestown, W. Va.

well on the E. Balnes Tract

containing 136 acres. Location \_\_\_\_\_

Danielle District, in Monongalia County, West Virginia

The surface of the above tract is owned in fee by Frank J. Jambry of Madestown, W. Va. address, and the mineral rights are owned by \_\_\_\_\_ of \_\_\_\_\_

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. No permit required issued by the West Virginia Department of Mines, Oil and Gas Division \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Elevation of surface at top of well 1705 ± \_\_\_\_\_ feet

The number of feet of the different sized casings used in the well \_\_\_\_\_

\_\_\_\_\_ feet \_\_\_\_\_ dia. Wood casing

2227 feet 5 3/16 dia. reg 2028 feet 5 5/8 steel cas.

\_\_\_\_\_ feet \_\_\_\_\_ dia. reg \_\_\_\_\_ feet \_\_\_\_\_ steel cas.

\_\_\_\_\_ feet \_\_\_\_\_ dia. reg \_\_\_\_\_ feet \_\_\_\_\_ steel cas.

\_\_\_\_\_ packer of \_\_\_\_\_ dia. set at \_\_\_\_\_

\_\_\_\_\_ packer of \_\_\_\_\_ dia. set at \_\_\_\_\_

\_\_\_\_\_ in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet

\_\_\_\_\_ in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet

Casing was cemented at 754 feet, 24th zone 50 inches, and at 2028 feet; thickness 26 inches; and at 1095 feet; thickness 26 inches

\_\_\_\_\_ Lenses were used as follows: (Give details) 2028 \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

March 11, 1958

Date

*Arthur Jambry*

3-13-58

*Arthur Mackey*

2400... Company

20420000 *2191A* Address

Well No. 2042

COMPLETION DATA SHEET  
NO. 2  
FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Fairview coal				754	759	5		
Dapleton coal				1013	1021	8		
Pittsburgh coal				1096	1105	9		
Little Dunard sand				1506	1540	34		
Big Dunard Sand				1590	1640	50		
Gas sand				1788	1850	62		
First salt sand				1910	1960	50		
Second salt sand				1970	2085	115		
Red rock				2120	2190	70		2-2'- 6 1/2"
Little lime				2282	2292	10		
Big lime				2390	2398	8		
Big Lamin				2588	2600	12		
Gants sand				2900	2945	45		2327 - 6 1/2"
Fifty foot sand				3048	3161	113		
Gordon clay				3191	3207	16		
Gordon sand				3269	3282	13		
Fourth sand				3239	3209	30		
Fifth sand				3284	3408	124		
Total depth							3621	

2-13-31

Well was shut at all feet      Shut well was shut at \_\_\_\_\_ feet

First water at \_\_\_\_\_ feet      Shut first water at \_\_\_\_\_ feet

Well was producing oil      Shut

March 11, 1938  
Approved Arthur Mackey

2400-20 Bulletin Revisions used for well in this report.

