

Part of **MAPS 17, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100**

of the

**MOORE CONSTRUCTION Co. SPRINGFIELD, W. Va.**

County, W. Va.

**PHILIP SHUMAN**

Part including of **87** Acres

**CLAY**

State

**ARMONSBALL**

County, W. Va.



**LEGEND**

- Location
- Oil Well
- ⊙ Abandoned
- ⊗ Gas Well
- ⊙ Abandoned
- ⊗ Dry Hole

Field Book No. 326, 87

Scale 1" = 400'

April 21, 1935

Well No. 387  
 " " 389  
 " " 390  
 " " 391

Abandoned April 1935

**ENGINEER'S CERTIFICATE**

I, the undersigned, hereby certify that this map is correct and shows all the information to the best of my knowledge and belief, required by the oil and gas sections of the mining laws of West Virginia.

**W. H. B. Co.**  
ENGINEERS

LATITUDE 39°42'30"

75'

11°00.51'08"

LONGITUDE

7'5 OGIS topo location

7.5' 10C  $\frac{0.365}{0.17W}$

15' 10C  $\frac{3.265}{0.17W}$   
(calc.)

Company \_\_\_\_\_

Farm \_\_\_\_\_

Quad Wadestown (Morningside NE)

County Monongahela

District Clay

WELL LOCATION MAP

File No. 061-128A

Clay District, Monongalia County, W. Va.  
 Hope Cons. & Ref. Co., 445 W. Main St., Clarksburg, W. Va.  
 On 87 acres, surface and mineral rights owned by W. M. Shuman,  
 Blacksville, W. Va.

Elevation, 1349' L.

10" casing, 1436' (571' pulled) (865' left in); 6-5/8", 2290';  
 5-3/16", 3208'; 2" tubing, 3337'; 4 1/2" x 4" liner, 138'.

Coal was encountered at 492-498, 600-605, 680-685, 932-937,  
 and 1030-1037'.

Abandonment reported to Dept. of Mines July 29, 1935.

Well was shot at 3327-3334'.

Fresh water at 1032'; salt water at 1917 and 2410'.

Oil well. Now exhausted.

MON-128-A

	Top.	Bottom.
Coal	492	498
Coal	600	605
Coal	680	685
Coal	932	937
Pittsburgh Coal (water, 1032')	1030	1037
Little Dunkard Sand	1450	1460
Big Dunkard Sand	1546	1602
Gas Sand	1785	1818
First Salt Sand	1824	1863
Second Salt Sand (water, 1917')	1915	1940
Maxton Sand	1955	2027
Little Lime	2255	2260
Pencil Cave	2260	2267
Big Line	2267	2315
Big Injun Sand (water, 2410'; show oil and gas, 2410')	2315	2545
Squaw Sand	2580	2662
Gantz Sand	2829	2852
50-Ft. Sand (gas, 2979-2985')	2950	3028
30-Ft. Sand	3049	3169
Gordon Stray Sand (show oil, 3197')	3179	3204
Gordon Sand	3220	3250
4th Sand (oil, 3330'), to bottom	3312	3337

Farm \_\_\_\_\_

Quad Wadestown (Marlington NE)

County Monongahela

District Clay

WELL LOCATION MAP

File No. 061-128A

## WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

## PRELIMINARY DATA SHEET NO. 1

File No. \_\_\_\_\_ Well No. 207New Construction & Refining Co. Company of 442 West Main St.Glensburg, W. Va., on the Phillip Shuman Farmcontaining 27 acres. Location \_\_\_\_\_Glaz District, in Wenona County, West VirginiaThe surface of the above tract is owned in fee by W. H. Shumanof Martinsburg, W. Va., address, and the mineral rights are owned byW. H. Shuman of Martinsburg, W. Va.,

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. \_\_\_\_\_ issued by the West Virginia Department of Mines, Oil and Gas Division

\_\_\_\_\_

Direction of surface at top of well. 1200 South  
Wenona

The number of feet of the different steel casings used in the well.

\_\_\_\_\_ feet \_\_\_\_\_ dia. Wood casings.

1000 feet 10" dia. exp. 2000 feet 6-5/8" steel exp.2000 feet 8-5/8" dia. exp. 2007 feet 8" steel exp.100 feet 4-1/2" Liner dia. exp. \_\_\_\_\_ feet \_\_\_\_\_ steel exp.

\_\_\_\_\_ galvanized \_\_\_\_\_ dia. set at \_\_\_\_\_

\_\_\_\_\_ galvanized \_\_\_\_\_ dia. set at \_\_\_\_\_

\_\_\_\_\_ in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet

\_\_\_\_\_ in casing perforated at \_\_\_\_\_ feet to \_\_\_\_\_ feet

Casing was encountered at 200 feet, which was 8 inches, and at 2000feet; thickness 2 inches; and at 1000 feet; thickness 2 1/2 inches.

Liners were used as follows: (Give details)

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

July 27th, 1928.

Data.

Approved \_\_\_\_\_  
New Construction & Refining Co., Owner

Hope Construction &amp; Refining Co. Company

Clatsburg, W. Va.

Address

## COMPLETION DATA SHEET

NO. 2

WELL NO. 267FARM Phillip Shuman

## FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Coal				482	488	6'		
Coal				600	606	6'		
Coal				680	686	6'		
Coal				908	907	5'		525' - 5" A
Pittsburgh Coal			Water - 1038	1030	1037	7'		
Little Dunkard Sand				1480	1440	10'		1436' - 10"
Big Dunkard Sand				1546	1808	26'		
Gas Sand				1768	1818	50'		
First Salt Sand				1884	1888	50'		
Second Salt Sand			Water - 1917	1918	1940	22'		
Heavy Sand				1988	2087	78'		
Little Lime				2208	2280	5'		
Fossil Cove				2280	2307	7'		
Big Lime				2307	2315	60'		1240' - 5 1/2"
Big Injun Sand			Water - 2416 Show Oil & Gas 2416	2315	2648	200'		
Sugar Sand				2680	2688	88'		
Gravel Sand				2820	2828	28'		
Fifty Foot Sand				2880	2888	78'		
Thirty Foot Sand			Gas - 2970 - 2925	2848	3148	180'		
Carbon Slug Sand			show oil - 3197	3178	3204	28'		3208' - 5 1/2"
Carbon Sand				3280	3288	28'		
Fourth Sand			Oil - 3288	3218	3287	28'		18' - 0 1/2" of line

shot  
Well was not shot at \_\_\_\_\_ feet; well was shot at 2827-2828 feet.

Water  
Fresh water at 1038 feet; fresh water at 1917 & 2416 feet.

producing  
Well was \_\_\_\_\_ lbs. Now estimated.  
day

July 28, 1928.

Approved: Hope Construction &amp; Refining Co.

By \_\_\_\_\_

Notes: The following information must be noted as indicated above and all log-books and all and gas logs must be filed in the district as well as any local sources commonly used in the district for each state.

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL.**

(PREPARED BY GEORGE S. ARNOLD & COMPANY AS OF THE CODE)

**WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION**

No coal operations in this section.

COAL OPERATOR OR OWNER

ADDRESS

COAL OPERATOR OR OWNER

ADDRESS

COAL OPERATOR OR OWNER

ADDRESS

**None Construction & Refining Company**

NAME OF WELL OPERATOR

Clarksburg, W. Va.,

EMPLOYED ADDRESS

October 24th, 1922

19

WELL AND LOCATION

Clay

District

Monongalia

County

Well No. 207

Phillip Shuman

Name

APPROVED BY ME HEREIN IN TRIPPLICATE, THIS COPY TO BE MAILED BY REGISTERING WITH THE SUPERVISOR, ONE COPY TO BE DEPOSITED IN THE FIELD OFFICE AND THE OTHER COPY AND OTHER COPIES OF RECORDS TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED BY THEIR RESPECTIVE ADDRESSES.

**AFFIDAVIT**

STATE OF WEST VIRGINIA,

County of Monongalia

vs:

John F. Shisler

and Lester B. Steel

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by None Construction & Refining Co., well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

24th day of July 1922

19

and that the well was plugged and filled in the following manner:

Manner in which said well was plugged: Removed 5" tubing, left 100-11/16 feet 4 1/2" X 4" liner in hole, unable to pull 6-3/16" Casp. Placed Wood & Cement Plug, at 2575' in top of lower Ripped 6-3/16" Casp. at 2100' & Pilled, leaving 100-0/16 ft. in hole, unable to place plug at 2100 account of savings, Bridged hole at 2000'-00' Below fifty feet sand, filled with clay to 2020' placed Sumner Sand and cement plug, Bridged hole at 2070'-00' Below Big Injun Sand, Filled with clay to 2000'-10' Above Big Injun Sand, Placed Wood and Cement plug, unable to pull 6-3/8" Casp. Ripped same at 2000' and pulled up to 1900' leaving 250' in hole, Bridged hole at 1970'-00' Below Salt Sand, Filled with clay to 1800'-00' Above Salt Sand, Placed Cement plug, Bridged hole at 1800' and Placed Cement Plug, unable to pull out via pump; Bridged hole at 1600'-00' Below Pittsburgh Coal Seam, Filled with cement to 600' Filled with clay to 600', Filled with Cement to 600', Filled with Clay to 710', Filled with cement to 600', Filled with clay to 600', Filled with Cement to 600', Filled with clay to 600', Filled with cement to 600', and Filled with clay from 600' to the surface.

The 6-3/8" Casp. was pulled in course of Plugging Coal Seam.

Description of monument:

Erected Cement Monument Size 8 X 8" X 60"-60" of which extends above the ground, with the following inscription,  
(None Construction & Refining Co. Well No. 207)

THIS ABOVE DESCRIPTION MUST BE IN DETAIL AND CORROBORATED UPON THE PREPARATION OF GEORGE S. ARNOLD & COMPANY AS OF THE CODE

and that the work of plugging and filling said well was completed on the 24th day of October, 1922

19

And further



Lester B. Steel  
John F. Shisler  
Phillip Shuman

Sworn to and subscribed before me this 17 day of October, 1922