


LATITUDE 39°42'30"

450



LONGITUDE

7'5 OGIS topo location

7.5' loc	$\frac{0.535}{0.26W}$	15' loc	$\frac{3.415}{2.50W}$
		(calc.)	

Company _____

Farm _____

Quad Blacksville (Blacksville NW)

County Monongahela

District Clay

WELL LOCATION MAP

File No. 061-132A

Plot showing the location of Well No. 2 of the
 receiver of the Moore-Paul Oil Company of Morgantown, West
 Virginia, to be abandoned on the 2.2 Acres farm of 20-2-4 acres
 located in Clay District, Boone County, West Virginia.



WITNESSES & DECLARATION.

I, the undersigned having verified that this map is correct
 and shows all the information to the best of my knowledge and
 belief required by the law and the location of the Mining Lease
 of West Virginia.

[Handwritten signature]

Witnessed before me a Notary Public, on and for
 Boone County, West Virginia, this 11th day of
 May, 1938.
 My Commission Expires

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. 202107 Well No. 2

By Wm. S. Glasscock Jr.,
Special Inspectors of Company of Wetzelton, W. Va.
More-Sea Oil Company

at the E. S. Sprank well
(formerly Mr. Myers)
containing 20 1/4 acres. Location 1 mile south of Blacksville W. Va.

Clay District, Wetzelton County, West Virginia

The surface of the above tract is owned in fee by E. S. Sprank
of Blacksville W. Va. address, and the mineral rights are owned by

Sealed Co. (formerly Clay District Seal Co.) of Pittsburgh, Penna.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit
No. before permits were issued by the West Virginia Department of Mines, Oil and Gas Division

March 1921

Depth of surface at top of well 1150 feet

The number of feet of the different sized casings used in the well:

Size	Depth	Material	Notes
16	feet	of conductor	also West casing
4 1/2	feet	to 1/2"	also steel cas.
10 1/2	feet	to 5/8"	also steel cas.
20 1/2	feet	to 1 1/8"	also steel cas.
30 7/8	feet	2" tubing	
		piece of	also, oil etc.
		piece of	also, oil etc.
		to casing perforated at	feet to
		to casing perforated at	feet to

Pittsburgh coal to casing perforated at feet to Sevitts coal

that was encountered at 200 feet, that was 2 1/2" tubing, and at 200

feet, thickness 6 1/2" tubing, and at feet thickness feet

Items were used as follows: (give details) 2000

September 29, 1921

Wm. S. Glasscock and
Special Inspectors of

Subt. J. Henson and
 Wm. B. Glascock Jr.,
 Special Receivers of
 Moore-Tex Oil Company

BOOK #2

OIL OR GAS WELL See Well

Company: Morgantown, W. Va.
 Address: R. E. Brock
 (Formerly Sub. Meyers)
 COMPLETION DATA SHEET
 No. 2
 FORMATION RECORD

WELL NO. 2

Name	Color	Character	Oil Gas or Water	Top	Bottom	Thickness	Feet Thick	Remarks
Swickley coal	.	.	.	705	711	6	711	6' 7" - 6' 11"
Pittsburgh coal	.	.	.	800	808	8	808	
Murphy sand	.	.	.	890	920	30		
Little Duckard sand	.	.	.	1130	1460	130		
First Salt sand	.	.	.	1970	1807	237		18' 11" - 20'
Little Lino	.	.	.	2002	2006	4		
Fencil Cove	.	.	.	2006	2032	6		
Big Lino	.	.	.	2032	2083	51		
Big Injun sand	.	.	.	2083	2313	230		22' 4" - 23'
Hayard sand	.	.	.	3205	3232	7		
Gas at	.	.	gas	3206	3220			gas - 10'
total depth.....							3220	

Well was set at 3224-3230

Fresh water at

original production was gas

September 26, 1935

Subt. J. Henson and
 Wm. B. Glascock Jr.,
 Special Receivers of
 Moore-Tex Oil Company

Form 60

**AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

132-

PREPARED BY GEORGE S. ARNOLD & COMPANY AS OF THE DATE

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION**

Coalwood Co., Inc.
(Formerly Clay District (L) Co.)

Geo. S. Arnold and
Company, Inc.,
1000 11th Street, N. W.,
Washington, D. C.

Union Industrial Lumber Co.,
Martinsburg, W. Va.

P. O. Box 872, Charleston, W. Va.

OIL OPERATOR OR OWNER

BY

NAME

WELL AND LOCATION

E. S. Beck

NAME OF OPERATOR OWNER

CLAY STATE

Stonewall, W. Va.

ADDRESS

WELL NO.

DATE


TESTED BY

**THIS IS TO CERTIFY THAT THE ABOVE NAMED PARTY HAS
AFFIDAVIT**

STATE OF WEST VIRGINIA
County of Marshall

I, E. S. Beck do hereby certify that the above named party has
affidavit of well plugged and filled in accordance with the provisions of
the laws of this State, and that the well was plugged and filled
on the _____ day of _____, 1935.

There is attached hereto a copy of the
logs and reports of the well from the bottom 200' to top
of the well, and from the top 200' to 300'
and the well was plugged and filled



Description of operation:
A concrete anchor was set. This extends 30 inches above the
ground surface and has a width at the top of 6" x 6".

and that the well of plugging and filling and well was completed on the _____ day of _____, 1935



A. S. Beck

Signature