

Clay District, Monongalia County, W. Va.

By J. H. McDermott Oil Co.; succeeded by Consolidation Oil & Gas Co.

On west side of Dunkard Creek, 0.8 mi. W. of Holman.

Completed, Nov. 29, 1922.

Elevation, 927' L.

Conductor, 16"; 10" casing, 480' (pulled); 8½", 1167' (pulled
except 307'); 6-5/8", 1680'; 5-3/16", 2596'; 4" liner, 298';
2" tubing, 2860'.10' working barrel; 28' anchor; perforation at 2880'; airmhole at
28.....1

Oil well, 15 bbls.

	Top.	Bottom.
Coal, Waynesburg	135	- 140
Coal, Mapletown (Sewickley)	390	- 395
Coal, Pittsburgh	473	- 482
Sand, Murphy	710	- 760
Gas Sand	1165	- 1215
Sand, First Salt	1275	
Sand, Second Salt	1370	- 1455
Big Line	1675	- 1725
Sand, Big Injun (oil and water, 1845-- 10 bbls.)	1725	- 1935
Sand, Squaw	1990	- 2030
Sand, Fifty-foot	2315	- 2460
Sand, Thirty-foot	2465	- 2510
Sand, Gordon Stray	2585	- 2610
Sand, Gordon	2625	- 2650
Sand, Bayard (oil, 2870 and 2879')	2865	- 2891
Total depth		2898

Oil

WELL RECORD 61-70085

The J.H. McDermott Oil

COMPANY

Record of Well No. 4 on J.W. Price Farm 48 Acres
 Field Clay District Monongalia County W.V. State
 Rig Commenced Mooreville ~~XXXXXXXXXXXXXXXXXXXX~~ Completed August 10th.
 Drilling Commenced August 14th. Completed November 20th.
 Cost Per Foot 19 22 Contractor Address
 Drillers Names B.F. Moslander and R.A. Cross

CONDUCTOR AND CASING USED IN DRILLING

Conductor	13 inch	10 inch	8 1-4 inch	6 5-8 inch	5 3-16 inch	4 inch	3 inch	2 inch
	16	480	1167	1680	2506			

CONDUCTOR AND CASING LEFT IN WELL

Conductor	13 inch	10 inch	8 3-4 inch	6 5-8 inch	5 3-16 inch	4 inch	3 inch	2 inch
-----------	---------	---------	------------	------------	-------------	--------	--------	--------

Formation	Top	Bottom	Thickness	Formation	Top	Bottom	Thickness
GRAVEL OR QUICK SAND				FORMATION			
FIRST WATER				SQUAW	1990	2030	
BLUFF SAND				BEREA			
NATIVE COAL				GANTZ			
WBG. COAL	175	140		FIFTY FOOT	2315	2460	
MAPEL COAL	300	305		THIRTY FOOT	2465	2510	
PGH. COAL	473	482		GORDON STRAY	2585	2610	
MURPHY SAND	710	760		GORDON	2625	2650	
LITTLE DKRD.				FOURTH			
BIG DKRD.				FIFTH	2245	2322	
GAS SAND	1165	1215		BAYARD	2865	2891	
FIRST SALT SAND	1275			0:1	2870		
SECOND SALT SAND	1370	1455		2 oil	2870		
LITTLE LIME				ELIZABETH			
PENCIL CAVE							
BIG LIME	1675	1725					
BIG INJUN	1725	1935					
Oil & Water	1845	10 bbls.					
				TOTAL DEPTH	2898		

Gas Test Open
 Minute Test
 Oil Production 15 bbls.
 Well Tubed with 2860 Tubing Packer Set in 10 Ft. working bbl. Sand, Top of Packer, 2880 Perforation
 Well Tubed with 2860 Tubing 10 Ft. working bbl. Anchor, Perforation at, 2880 Air Hole 28'

SHOT RECORD

Date	Amount	Size of Shell	Top	Bottom	Oil on Shot	Results
Jany. 16th. 23	20 qts.	4' x 7'	2870	2886	5 to 15 bbls.	150'
July 15/24	28" sol.		2876	2886	140 ft.	1'
<i>could not get shot run 20 qts. more to get shot off. shot July 26, 1924.</i>						
Abandoned in 1922						

REMARKS: 4" liner in hole 298' two bottom jts. perforated, steel bell on top, on 5" casing fractured with one hole July 15/24 at 1830,