7'5 OGIS topo location

7.5' loc 0.855 15' loc 3,735 (calc.) 4.31 W #183 on 1912 Co. Ppt. 2.09 W

Company

Quad GRANT TOWN (BULLE WE)

County Monorganela

District Clay

WELL LOCATION MAP File No. 061-70131

No. 77 O.F.-Marion. No. 183 M-M-T Rept., p. 480.

By Fisher Oil Co.
Elevation, 1055; B. 1.5 mi. N. of Fairview.
Commenced Aug. 25, 1903; completed, Dec. 14, 1903.
Contractor, E. M. Smith.
Filled up 800 feet with oil and water from Injun pay.
Filled up 1200 feet with oil from Bayard Sand the first 12 hrs; no gas at all.
Bottom hole packer put in with 5-3/16" casing.
From bottom of casing to top of Bayard, 996 feet.
Bottom of liner 2975; below surface of hole and 2405; below top of Pittsburgh Coal.

10' conductor; 10" casing, 580; 81", 1075; 6-5/8", 1560; 5-3/16", 1985; hm liner, 523; in two sections, 271; in 1st and 252; in 2nd; bottom joint perforated.

Bhot Mar. 26, 1904, by C. C. Fisher, with 24 qts., 12; shell, 4; anchor; depth of well when shot, 2997; depth, top of shot, 2981; good results.

		Top. Bottom.
	Pittsburgh Coal	570 - 578
	Big Injun Sand (pay, 1969-1973)	1895 - 2015
	Gordon Sand	2780 - 2800
	Fourth Sand	2830 - 2860
Tifth.	Bayard Sand (pay, 2981-2985')	2981 - 2985
y	Total depth	3003