

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

TUNNEL RIDGE, LLC  
Coal Operator or Owner  
2596 BATTLE RUN RD, TRIADELPHIA, WV 26059  
Address

TUNNEL RIDGE, LLC  
Coal Operator or Owner  
2596 BATTLE RUN RD, TRIADELPHIA, WV 26059  
Address

GLENN DILLE  
Lease or Property Owner  
190 GOBBLER KNOB, VALLEY GROVE, WV 26060  
Address

TUNNEL RIDGE, LLC  
Name of Well Operator  
2596 BATTLE RUN RD, TRIADELPHIA, WV 26059  
Complete Address

BETHANY 7.5'  
Well Location  
LIBERTY  
District  
OHIO  
County  
FOSTER #1  
Well No.

ETHEL M. FOSTER  
Farm

STATE INSPECTOR SUPERVISING PLUGGING \_\_\_\_\_

AFFIDAVIT

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

RUSSELL SMALLWOOD and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 5<sup>th</sup> day of June, 2015 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Formation				
Cleaned 7 7/8" hole from Surface to 891'. Tagged solid plug at 891'. Cut 8 5/8" casing at the following depths: 216' and 92'. Attempted to remove 8 5/8" casing. No 8 5/8" casing was able to be removed due to extreme bond from previous cementing. Section milled 46' of 8 5/8" casing from 615' to 661'. Section milled with 9 1/2" mill through the Pittsburgh Coal seam from 629' to 634'. Cut remaining 8 5/8" casing at the following depths: 834', 784', 734', 684', 579', and 529'. Left approximately 954' of 8 5/8" casing in the hole from Surface to 615' and 661' to ~1000'. Depth of 8 5/8" casing taken from previous well record. Left an unknown amount of 13 3/8" casing in the hole from Surface to an unknown depth. Left 10' of 16" conductor casing in the hole from Surface to 10'.	8 5/8"	0'	~954'	
		13 3/8"	0'	Unknown
		16"	0'	10'
<p><u>Cemented hole from 891' back to the Surface as follows:</u> From 891' to 529' with 105 sacks of Thixotropic Cement with green dye. From 529' back to the Surface with 125 sacks of Expandable Cement. Cement did circulate at the surface.</p>				
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	(629' - 634')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

Received  
JUL 23 2015  
Office of Oil and Gas  
WV Dept. of Environmental Protection

... and that the work of plugging and filling said well was completed on the 15<sup>th</sup> day of June, 2015.

And further deponents saith not.

Russell Smallwood  
Russell Smallwood

Kevin S. Wright  
Kevin S. Wright

07/24/2015

Sworn to and subscribed before me this 6 day of July 2015

Kara Beth Forst  
Notary Public

My commission expires: 11/4/23



Permit No. 47-069-00028-P  
Well No. FOSTER #1